

PCI-600B - [click here](#)

Processor: Supports Intel Pentium Pro up to 300 MHz

Chip set: Intel Natoma chip set 440FX Fully complies with PCI local bus specification 2.1

Main memory: One 168-pin DIMM socket and four 72-pin SIMM sockets support 8 to 768 MB EDO/BEDO/FPM/HPM DRAM with automatic DRAM configuration, ECC support


System BIOS: Award BIOS supports full green function, plug-&-play function, adaptec SCSI BIOS, NCR SCSI BIOS, and Fast ATA-II IDE specification

Expansion slots: Four 16-bit ISA slots Four 32-bit PCI master slots

Super multi-I/O: Winbond W83877F/W83877AF Plug-and-play power-I/O chip 2S/1P/1G (fast UART 16550 compatible serial ports, EPP/ECP parallel port) Supports two 3.5 or 5.25-inch FDDs with 2.88 MB FDC Supports IrDA(HPSIR and ASKIR) serial infrared communication (115.2 Kbps)

USB: Two built-in USB (Universal Serial Bus) connectors

PCI SCSI-III Adaptec: Fastest IDE controller complies with 32-bit PCI specification 2.1 Supports up to four Fast ATA-2 and ATAPI devices Supports DMA master mode 2 with data transfer rate up to 22 MB/s, PIO modes 3 and 4 with data transfer rate up to 17 MB/s,

PCI SCSI-III Adaptec:  Adaptec master device combines PCI interface with Ultra SCSI (optional) AIC7860 Ultra SCSI controller EZ-SCSI software Package and Adaptec 7800 family manager set support Corel SCSI leading SCSI software to support every peripheral

Form factor: Baby AT form factor, 8.7x13 inches