

[PCI-600-F](#) - click here

Processor:	Supports all Intel Pentium II CPU from 233to 450 Mhz
Chip set:	Intel 440 BX 66/100 MHz system clock supported. Fully complies with PCI Bus spec. V2.1. AGP specification V1.0 compliant.
On board IDE:	2 connectors support up to 4 fast ATA-2 and ATAPI devices. Supports PIO mode 3 and 4 devices, data transfer rate can be up to 33MB/s.
System memory:	Four DIMM Sockets. Support 3.3v SDRAM DIMM module. Memory Size: 8 MBytes to 256 MBytes (with 16 Mbit Technology).
On board I/O:	SMC FDC602 power I/O 1 floppy port (2.88MB floppy optional). 2 serial ports (16550 fast UART compantible). 1 parallel port (SPP/EPP/ECP mode). 1SIR port (transfer rate up to 115KByte/s) 1 PS/2 mouse port & 1 PS/2 K?B port. 2 USB port.
BIOS:	AWARD green BIOS support Plug & Play function.
Expansion slots:	4 PCI master slots (PCI spec. V2.1) 3 ISA Bus Slots (1PCI/ISA Shared slot). 1 AGP (Accelerated Graphics Port)
SCSI:	Adaptec AIC-7880 ULTRA WIDE SCSI (option)
Board size:	ATX form factor 30.5 X 21.5