

 PHOTO

BENCH MARKS

DOWNLOAD/
JUMPERS

- Processor:** Intel Pentium II CPU from 233 to 450MHz and up
- Chip set:** VIA Apollo Pro
66/75/83/100/103/112/124/133MHz
system clock supported
Fully complies with PCI Bus spec. V2.1
AGP specification V1.0 compliant
- On board IDE:** 2 connectors support up to 4 Ultra DMA and fast ATA-2 devices.
Supports PIO mode 3 and 4 devices, data transfer rate can be up to 17 MB/s
Supports Ultra DMA, data transfer rate can be up to 33MB/s.
- System Memory:** 3 DIMM Sockets
Supports 3.3V SDRAM DIMM module
Memory size: 8 MBytes to 192 Mbytes (with 16 Mbit Technology)
8 MBytes to 768 Mbytes (with 64 Mbit Technology)
- Intergrated I/O:** SMC FDC 669 power I/O chip
1 floppy port (2.88MB floppy optional)
2 serial ports (16550 fast UART compatible)
1 parallel port (SPP/EPP/ECP mode)
SIR port (transfer rate up to 115KByte/s)
1 PS/2 Mouse. 1 PS/2 K/B port
1 IrDA port
2USB Ports
1 Creative SB-Link Connector
- BIOS:** AWARD green BIOS support Plug & Play Function.
Supports Flash memory for easy upgrade.
Supports Jumpless CPU Frequency Setting.
- System Protection (option):** Monitoring the System and CPU Temperature,
CPU voltage, system voltage, CPU fan RPM, system fan
- Expansion slots:** 3 PCI master slots (PCI spec. V2.1)
2 ISA Bus Slot
1 133MHz AGP (Accelerated Graphics Port)
- 3D Sound Build-in (optional):** CMI8330 DX 3D Sound Chip onboard
Supports S/W Wave-Table
Supports Mic; Line Input; Speaker out; Bame Port
- Board Size** Micro ATX (244 x 190mm)(Fits in standard ATX casing as well)

