

ISA 486/5x86 CPU Card With VGA (onboard 133MHz CPU)

	*
Specifications:	
CPU Type:	Built-in AMD 5x86-133 MHz
CPU Voltage:	3.3V.
Power Requirement:	+5V and +12V
DRAM:	Up to 128MB in two 72-pin SIMM sockets
Cache:	L1 Cache: 16KB Cache, L2 Cache: 128KB Cache.
BIOS:	Award PnP BIOS, Flash ROM, with VGA BIOS
S/IO Setup:	By software configuration
IDE Interface:	One Enhanced IDE, support 2 devices
FDD Interface:	Supports up to two floppy disk drives
Serial Port:	Two 16550 UART, w/ COM2 selectable for RS232/422/485
Parallel Port:	Bi-directional; Supports SPP/EPP/ECP.
Watchdog:	16 level Watchdog Timer
CMOS:	Real Time Clock/Calendar
Keyboard:	Mini DIN connector and external connector
Mouse:	Mini DIN connector (selectable w/ Keyboard)
Speaker:	Internal Buzzer & external speaker connector
VGA:	C&T 65550 1M DRAM for CRT & LCD
Panel Display:	STN, TFT, EL modes
SSD:	32-pin DOC socket supports up to 144MB
Bus Interface:	ISA Bus; PC104 Bus
Green Function:	Controlled by Hardware & Software

Dimension:	185mm x 122mm
Ordering Information:	
JJ-141A	
ISA 486/5x86 CPU Card With VGA	

Menu