


M815A

Industrial ATX Board for Pentium® !!! Processor



Specifications:

◆ Processor:

- Intel® Celeron™ Processor with PPGA/FCPGA socket 370 packing: operating at 433 ~ 1.1GHz
- Intel® Pentium® !!! /Coppermine™ Processor with FC-PGA socket 370 packing: operating at 500MHz ~ 1.1GHz

◆ Core Logic:

- Intel® 82815EP AGPset

◆ BIOS:

- Award BIOS

◆ FSB:

- 66 / 100 / 133 MHz

◆ Memory:

- Three 168-pins DIMM sockets, support up to 512MB

◆ IDE:

- PIO Mode 0-4, DMA Mode 0-2 and two channels for Ultra DMA-100 up to 4 IDE devices

◆ Multi I/O:

- Onboard Winbond 83627HF-AW LPC chip, Support:
 - 1x Floppy Interface
 - 1 x SPP / EPP / ECP parallel port
 - 2 x 16550 UART compatible serial ports
 - Fast IR and Power-On

◆ Keyboard Connector:

- Onboard 1 x 6-pins mini DIN (PS/2 type connector)

◆ Mouse Connector:

- Onboard 1 x 6-pins mini DIN (PS/2 type connector)

*Specification is subject to change without prior notice

◆ USB:

- 4 x USB ports (2 for Opt.)

◆ Built-in AC97 Digital Audio:

- Dual full-duplex Direct Sound channels
- H/W Sound Blaster Pro for DOS legacy compatibility
- FM synthesis for legacy compatibility
- Support game and MIDI port

◆ SSD:

- 32-pins socket for flash disk 2MB ~ 288MB

◆ Expansion Slots:

- 2 x PCI slots (one shared) / 4 x ISA slots / 1 x AGP slot

◆ WatchDog Timer:

- 16 level software programmable

◆ Hardware Monitoring:

- Winbond W83627HF-AW chip, Monitoring for CPU and system temperature, voltage and fan speed

◆ Environments:

- Operation temperature: 0°C to 60°C,
- Storage temperature: -20°C to 80°C,
- Relative humidity: 10% to 90% (Non-Condensing)

◆ Certification:

- CE Approval, FCC Class A

◆ Form Factor:

- ATX form factor

◆ Dimensions (D x W):

- 9.1" x 12" (230mm x 305mm)

Ordering Information:

Model No.	Position	Support LCD	Support VGA	Support SCSI	Support LAN	Support RAID
① M815A	Standard Product					