Search HP.com

Product (e.g. Deskjet D2680)

Question or keywords

Contact HP

HP Consumer Support

Motherboard Specifications, A7V8X-LA (Kamet 2)

🔁 Print 🛛 🔁 Share

Mainboard specifications

Motherboard photos and layout

Mainboard specifications

PART / FEATURE	SPECIFICATION / SUPPORT	~
Motherboard Description	 MB manufacturer name: ASUS A7V8X-LA HP/Compaq name: Kamet2-GL6E 	Tips
CPU	 Socket A AMD Athlon/Athlon XP Barton core support Maximum approved processors: Athlon XP 3000+ Barton core (2.167 GHz, 333MHz) Athlon XP 2700+ Thoroughbred core (2.16GHz, 266MHz) 	We are currently updating our customer support system and are unable to process your service order at this time Please check back after September 14th (10:00 AM MT) for your order status Extend your warranty with HP Care Pack Services Check out the HP Total Care Support Videos
Chipset	VIA KM400VIA VT8237	Related support links
Front Side Bus (FSB)	• 333/266 MHz	Check warranty status
Memory	 Two 184-pin DDR DIMM Maximum memory size is up to 2GB, 1GB per slot. HP recommends a maximum memory of 1GB, 512MB per slot. Supports PC2700/PC2100/PC1600 Unbuffered non-ECC 	Check repair order HP Support forums Find solutions and collaborate with others on the HP Support Forum
Expansion Slots	 Three PCI slots One AGP 8X/4X slot (1.5V) 	Join the conversation
Storage	Two UltraDMA 100 connectors	

	Two Serial ATA connectors
Integrated Graphics	VIA UniChrome Graphics
IDE	 Two UltraDMA 100/66/33 connectors PIP Mode 3/4 Supports ATAPI IDE, CD-ROM, CD-R, CD-RW, and LS-120
Onboard Audio	 Digital audio via an S/PDIF out interface RealTek ALC658 6-channel audio CODEC subsystem
Onboard IEEE 1394	VIA VT6307Supports two 1394 ports
Onboard LAN	 VT6103 LAN PHY (Physical Layer Protocol) Integrated 10/100 Mbps LAN controller
Hardware Monitoring	 Super I/O Integrated monitoring: CPU and chassis fan rotations Motherboard/CPU temperature
Rear panel I/O	 One parallel port One serial port One video port One PS/2 keyboard One PS/2 mouse port One RJ-45 port Up to four USB 2.0 / USB 1.1 ports One IEEE 1394 port Audio line-in, line-out, and microphone ports
Internal I/O	 One USB 2.0 connector for two additional USB ports One IEEE 1394 connector CPU/chassis fan connectors 20-pin ATX 12V power connectors Front panel connector S/PDIF out connector CD/AUX audio connector Front panel audio connector
BIOS Features	 4Mb Flash ROM Award BIOS with Enhanced ACPI, PnP, DMI2.0, Green features
Form Factor	 Micro-ATX form factor 9.6 inches X 9.6 inches (24.5 cm x 24.5 cm)
Industry Standard	• USB 2.0/1.1

Follow us



• PCI 2.2

NOTE:Mainboard specifications are subject to change without notice

Back to top

Motherboard photos and layout

Figure 1: Motherboard layout




Figure 2: Overhead view




Figure 3: Color coded backplate



Back to top

United States Mobile version

About HP

Contact us Newsroom Investor relations Living Progress Accessibility Events HP Labs Jobs

Social Media

Consumer support forum Enterprise business community Corporate blogs

f in 🗾

HP Partners

Become a partner Find a reseller PartnerOne

Customer Support

Power cord replacement Download drivers Register your product Authorized service providers Training & certification Product recycling

Home | Email sign-up | Site map | Privacy | Cookies & ad choices | Terms of use | Recalls © 2014 Hewlett-Packard Development Company, L.P.

View mobile site