HP Consumer Support

Motherboard Specifications, MS-6577 (Xenon)

Print



Motherboard information

Layout and photographs

Clearing the CMOS settings

Clearing the BIOS password

Motherboard information

Feature/Specification	Description
Motherboard Description	 Manufacturer's name - MSI MS-6577 HP/Compaq name - Xenon
Motherboard Supplier	MSI
Motherboard Name	MS-6577 Rev 1
System BIOS Supplier	MSI/Award
Form Factor	uATX
Processor Brand	Intel
Processor Socket Type	mPGA478
Processor Family	P4 and Celeron (Willamette, Northwood)
Proc. Front Side Bus Frequency	400/533 MHz
Chipset Name	845G
Chipset "North Bridge"	845G
revision/stepping	A1
Chipset "South Bridge"	ICH4
revision/stepping	A1
Super I/O	Winbond
revision/stepping	W83627HF-AW
Flash BIOS Device	4MB Flash EEPROM
Memory Type	DDR
Memory Speed	PC2100/PC1600
Memory Sockets	2 DIMM
Maximum Memory	1 GB
Graphics Supplier	Intel
Graphics Configuration	Down, In Chipset

Contact HP

Question or keywords

Tips

We are currently updating our customer support system and are unable to process your service order at this time Please check back after September 14th (10:00 AM MT) for your order status

Extend your warranty with HP Care Pack Services

Check out the HP Total Care Support Videos

Related support links

Check warranty status

Check repair order

HP Support forums

Find solutions and collaborate with others on the HP Support Forum

Join the conversation

Follow us















Onboard Graphics Me	emory	UMA/up to 48MB
Graphics Connector (AGP)		AGP4x
TV-Out Device		No
TV-Out Configuration	ı	(N/A)
Audio		AC'97 Down
AC'97 CODEC Device		Realtek ALC202A
Audio Jacks (Legend	below)	M, LI, LO, SO
М	Microphone	
Ц	Line In	
LO	Line out	
S0	Speaker	
M/G	Midi/Game	
Ethernet 10/100 LAN	N Supplier	Realtek RTL8101L
Ethernet Configurati	on	PCI, Down
IDE UDMA Modes		ATA-66/100
Expansion Slots (AGP/PCI/Exten)		AGP, 3 PCI
USB Ports		6 USB 2.0
USB Front/Back Options		2F+4B
Serial, Parallel, Floppy, PS2 Keyboard and Mouse		1S, 1P, 1F, PS2 K+M
Serial Port Front Chassis Option		No
Available Manufactu	ring Options (Legend below)	-G, L, A
Α	Audio down on motherboard	
С	External L2 cache on motherboard	
E	1394 on motherboard	
G	Graphics down (on motherboard or in chipset)	
L	LAN on motherboard (Ethernet) P - PCMCIA slot	
S	S3 power management support	
Т	TV-out on motherboard	
U	Graphics card (up, not on motherboard)	
W	Microsoft® Windows XP hardware compliant	
		Back to top

Layout and photographs

Figure 1: Layout





Figure 2: Photograph



Figure 3: Backplate



1 - Mouse

2 - USB

- 4 LAN
 5 Line-in
 6 Line-out
 - 7 Microphone

3 - Parallel

- 8 USB
- 9 VGA
- 10 Serial
- 11 Keyboard

Back to top

Clearing the CMOS settings

The JBAT1 jumper allows you to clear the date, time, and system setup parameter memories in CMOS by erasing the RTC RAM data. The onboard button cell battery powers the RAM data in CMOS, including system setup information such as system passwords.

Back to top



CAUTION: Do not change any jumper setting while the computer is on. Damage to the motherboard can result.

- 1. Turn off the PC and unplug the power cord.
- 2. Move the JBAT1 jumper cap from pins 1-2 (normal) to pins 2-3 (clear CMOS).
- 3. Keep the JBAT1 jumper cap on pins 2-3 for 5 to 10 seconds, then move it back to pins 1-2.
- 4. Plug in the power cord and turn on the PC.
- 5. Enter **BIOS setup** to change BIOS settings.

Clearing the BIOS password

The BIOS password protects the BIOS from undesired changes. If password checking is enabled, and you need to disable it, use the following steps:

- 1. Turn off the PC and unplug the power cord.
- 2. Remove the JPWD1 jumper cap.
- 3. To enter BIOS setup, start the PC and press the F1 key as the PC boots.
- 4. Clear or reset the BIOS password.
- 5. Save the BIOS settings and turn off the PC.
- 6. Replace the JPWD1 jumper cap.



About HP

Contact us
Newsroom
Investor relations
Living Progress
Accessibility
Events
HP Labs
Jobs

Social Media

Consumer support forum Enterprise business community Corporate blogs



HP Partners

Become a partner Find a reseller PartnerOne

Customer Support

Power cord replacement
Download drivers
Register your product
Authorized service providers
Training & certification
Product recycling

Home | Email sign-up | Site map | Privacy | Cookies & ad choices | Terms of use | Recalls © 2014 Hewlett-Packard Development Company, L.P.

View mobile site