

Shuttle MS52P/N



Main characteristics

- **Form factor** μ ATX (244 x 244 mm)
- Supported Pentium 4 or Celeron **processors in 478-pin package with FSB (front side bus) speed of 400 or 533 MHz;** support for Hyper Threading technology
- **Chipset** SiS 651 + 962L
- DDR 200/266/333 (PC2700), two 184-pin SDRAM DIMM sockets, max . volume up to 2 GB
- **Disk controller** UDMA 133 (SiS 962L)
- **AGP 1.0/2.0 video slot** , 2x/4x modes, 3.3V/1.5V power supply
- **Integrated** SiS 3D video
- **Sound** 4-channel audio (AC'97)
- **BIOS** Award PnP, 2 Mbit LPC flash, floppy boot supported, ATAPI, USB, SCSI
- **Status monitoring** hardware

External interfaces

- **Ethernet (MS52PN only)** Realtek 8100B (10/100 Mbps)
- **USB 1.1/2.0** support six ports (SiS 962L)

Connectors

- **PCI Slots** - 3
- **PS / 2 keyboard / mouse** - 1/1
- **COM / LPT** - 1/1
- **USB 2.0** - 6
- **CNR (network extension)** - 1
- **Audio** line out, line in, microphone; game port