


P4C800-E Deluxe



Product support for

## P4C800-E Deluxe

[Find another model >](#)

By registering your device, you can easily manage your product warranty, get technical support and keep track of your repair status.

Register Product

CPU / Memory Support
Driver & Tools
FAQ
Manual & Document
Warranty

## CPU SUPPORT

The following table shows the supported CPUs for this motherboard [Click here to search other motherboards.](#)

CPU	Validated since PCB	Validated since BIOS	Note
Celeron 1.7 GHz (400 FSB, L2 cache:128KB)	ALL	ALL <a href="#">GO</a>	
Celeron 1.8 GHz (400 FSB, L2 cache:128KB)	ALL	ALL <a href="#">GO</a>	
Celeron 2.0 GHz (400 FSB, L2 cache:128KB)	ALL	ALL <a href="#">GO</a>	
Celeron 2.1 GHz (400 FSB, L2 cache:128KB)	ALL	ALL <a href="#">GO</a>	
Celeron 2.2 GHz (400 FSB, L2 cache:128KB)	ALL	ALL <a href="#">GO</a>	
Celeron 2.3 GHz (400 FSB, L2 cache:128KB)	ALL	ALL <a href="#">GO</a>	
Celeron 2.4 GHz (400 FSB, L2 cache:128KB)	ALL	ALL <a href="#">GO</a>	
Celeron 2.5 GHz (400 FSB, L2 cache:128KB)	ALL	ALL <a href="#">GO</a>	
Celeron 2.6 GHz (400 FSB, L2 cache:128KB)	ALL	ALL <a href="#">GO</a>	
Celeron 2.7 GHz (400 FSB, L2 cache:128KB)	ALL	1014 <a href="#">GO</a>	
Celeron 2.8 GHz (400 FSB, L2 cache:128KB)	ALL	1014 <a href="#">GO</a>	
Celeron D 310 revE0(2.13 GHz, 533 FSB, Socket478)	ALL	<a href="#">GO</a>	

CPU	Validated since PCB	Validated since BIOS	Note
Celeron D 310 revG0(2.13 GHz, 533 FSB, Socket478)	ALL	1024 	
Celeron D 315 (2.26 GHz, 533 FSB, Socket478)	ALL	1021 	
Celeron D 320 (2.4 GHz, 533 FSB, Socket478)	ALL	1017 	
Celeron D 325 (2.53 GHz, 533 FSB, Socket478, revC0/D0)	ALL	1017 	
Celeron D 325 (2.53 GHz, 533 FSB, Socket478, revE0)	ALL	1024 	
Celeron D 330 (2.66 GHz, 533 FSB, Socket478)	ALL	1017 	
Celeron D 335 (2.8 GHz, 533 FSB, Socket478)	ALL	1017 	
Celeron D 340 (2.93 GHz, 533 FSB, Socket478)	ALL	1018 	
Celeron D 345 (3.06 GHz, 533 FSB, Socket478)	ALL	1018 	
Celeron D 350 (3.20 GHz, 533 FSB, Socket478, revE0)	ALL	1021 	
Celeron D 350 (3.20 GHz, 533 FSB, Socket478, revG1)	ALL	1024 	
P4-1.4 GHz (Socket478, 400 FSB, L2 cache:256KB)	ALL	ALL 	
P4-1.5 GHz (Socket478, 400 FSB, L2 cache:256KB)	ALL	ALL 	
P4-1.6 GHz (Socket478, 400 FSB, L2 cache:256KB)	ALL	ALL 	
P4-1.6A GHz (Socket478, 400 FSB, L2 cache:512KB)	ALL	ALL 	
P4-1.7 GHz (Socket478, 400 FSB, L2 cache:256KB)	ALL	ALL 	
P4-1.8 GHz (Socket478, 400 FSB, L2 cache:256KB)	ALL	ALL 	
P4-1.8A GHz (Socket478, 400 FSB, L2 cache:512KB)	ALL	ALL 	
P4-1.9 GHz (Socket478, 400 FSB, L2 cache:256KB)	ALL	ALL 	
P4-2 GHz (Socket478, 400 FSB, L2 cache:256KB)	ALL	ALL 	
P4-2.20 GHz (400 FSB, L2 cache:512KB)	ALL	ALL 	

CPU	Validated since PCB	Validated since BIOS	Note
P4-2.26 GHz (533 FSB, L2 cache:512KB)	ALL	ALL <a href="#">GO</a>	
P4-2.40 GHz (400 FSB, L2 cache:512KB)	ALL	ALL <a href="#">GO</a>	
P4-2.40A GHz (533 FSB, L2 cache:1MB, 90nm)	ALL	1016 <a href="#">GO</a>	
P4-2.40B GHz (533 FSB, L2 cache:512KB)	ALL	ALL <a href="#">GO</a>	
P4-2.40C GHz (800 FSB, L2 cache:512KB, HT)	ALL	1010 <a href="#">GO</a>	
P4-2.50 GHz (400 FSB, L2 cache:512KB)	ALL	ALL <a href="#">GO</a>	
P4-2.53 GHz (533 FSB, L2 cache:512KB)	ALL	ALL <a href="#">GO</a>	
P4-2.60 GHz (400 FSB, L2 cache:512KB)	ALL	ALL <a href="#">GO</a>	
P4-2.60C GHz (800 FSB, L2 cache:512KB, HT)	ALL	1010 <a href="#">GO</a>	
P4-2.66 GHz (533 FSB, L2 cache:512KB)	ALL	ALL <a href="#">GO</a>	
P4-2.80 GHz (533 FSB, L2 cache:512KB)	ALL	ALL <a href="#">GO</a>	
P4-2.80A GHz (533 FSB, L2 cache:1MB, 90nm)	ALL	1017 <a href="#">GO</a>	
P4-2.80C GHz (800 FSB, L2 cache:512KB, HT, D1)	ALL	ALL <a href="#">GO</a>	
P4-2.80E GHz (800 FSB, L2 cache:1MB, HT, 90nm, CO)	ALL	1017 <a href="#">GO</a>	
P4-2A GHz (Socket478, 400 FSB, L2 cache:512KB)	ALL	ALL <a href="#">GO</a>	
P4-3 GHz (800 FSB, L2 cache:512KB, HT, D1/M0)	ALL	ALL <a href="#">GO</a>	
P4-3.06 GHz (533 FSB, L2 cache:512KB, HT, C1/D1)	ALL	ALL <a href="#">GO</a>	
P4-3.20 GHz (800 FSB, L2 cache:512KB, HT, D1)	ALL	ALL <a href="#">GO</a>	
P4-3.20 GHz Extreme Ed. (800 FSB, HT)	ALL	1016 <a href="#">GO</a>	
P4-3.20E GHz (800 FSB, L2 cache:1MB, HT, 90nm)	ALL	1017 <a href="#">GO</a>	
P4-3.40 GHz (800 FSB, L2 cache:1MB, rev.G1)	ALL	1024 <a href="#">GO</a>	

CPU	Validated since PCB	Validated since BIOS	Note
P4-3.40 GHz (800 FSB, L2 cache:512KB, HT, D1)	ALL	1016 <a href="#">GO</a>	
P4-3.40 GHz Extreme Ed. (Socket478, 800 FSB, HT)	ALL	1016 <a href="#">GO</a>	
P4-3.40E GHz (800 FSB, L2 cache:1MB, HT, 90nm)	ALL	1017 <a href="#">GO</a>	

Shop and Learn			Learn More	Support	About Us
<b>Laptops</b>	Tower PCs	WiFi Routers	Partner Portal	ASUS Premium Care	About ASUS
For Home	Mini PCs	Whole Home Mesh WiFi System	ASUS PC DIY	ASUS Repair Services	Careers
For Work	NUCs	AIoT & Industrial Solution	Become a Reseller	ASUS Support Videos	Corporate Social Responsibility
For Creators	Workstations	Servers	Edge Up	Commercial Support	News
For Students	<b>Motherboards / Components</b>	Smart Home	Insider's Edge	Contact Us	Internal Audit
For Gaming	Motherboards	<b>Accessories</b>	Powered by ASUS	Deal Registration	Press Room
<b>Mobile / Handhelds</b>	Gaming Case	Keyboards	Rate Your Gear	MyASUS	Where to Buy
Phones	Cooling	Mice and Mouse Pads	Accessibility Policy	Product Registration	ASUSTOR Inc.
Wearable	Graphics Cards	Headsets and Audio	AVC Licensing Notice	Rebate Center	
Accessories	Power Supply Units	Streaming Kit	ASUS Blog	Recalls	
<b>Displays / Desktops</b>	Sound Cards	Apparel, Bags & Gear		Security Advisory	
Monitors	Optical Drives	Cases and Protection		Warranty Extension	
Projectors	Data Storage	Adapters and Chargers			
All-in-One PCs	<b>Networking / IoT / Servers</b>	Docks, Dongles and Cable			
Gaming Tower PCs	WiFi 6				

