



Product Support For

## P4SGX-MX

[Find Another Model](#) >

Get Product Support

[Register Product](#)

CPU / Memory  
Support

Driver & Utility

FAQ

Manual &  
Document

## CPU SUPPORT

CPU Support

Memory / Device Support

### NEED HELP?

[Email Us](#)

[Find service locations](#)

The following table shows the supported CPUs for this motherboard [Click here to search other motherboards.](#)














CPU	Validated since PCB	Validated since BIOS	Note
-----	---------------------	----------------------	------

ALL

# P4SGX-MX

L2 cache:128KB)			
Celeron 2.0 GHz (400 FSB, L2 cache:128KB)	ALL	ALL	GO
Celeron 2.1 GHz (400 FSB, L2 cache:128KB)	ALL	ALL	GO
Celeron 2.2 GHz (400 FSB, L2 cache:128KB)	ALL	ALL	GO
Celeron 2.3 GHz (400 FSB, L2 cache:128KB)	ALL	ALL	GO
Celeron 2.4 GHz (400 FSB, L2 cache:128KB)	ALL	ALL	GO
Celeron 2.5 GHz (400 FSB, L2 cache:128KB)	ALL	1005	GO
Celeron 2.6 GHz (400 FSB, L2 cache:128KB)	ALL	1005	GO
Celeron 2.7 GHz (400 FSB, L2 cache:128KB)	ALL	1006.002	GO
Celeron 2.8 GHz (400 FSB, L2 cache:128KB)	ALL	1006.002	GO
P4-1.4 GHz (Socket478, 400 FSB, L2 cache:256KB)	ALL	ALL	GO
P4-1.5 GHz (Socket478, 400 FSB, L2 cache:256KB)	ALL	ALL	GO
P4-1.6 GHz (Socket478, 400 FSB, L2 cache:256KB)	ALL	ALL	GO
		ALL	

# P4SGX-MX

400 FSB, L2 cache:256KB)			
P4-1.8 GHz (Socket478, 400 FSB, L2 cache:256KB)	ALL	ALL	
P4-1.8A GHz (Socket478, 400 FSB, L2 cache:512KB)	ALL	ALL	
P4-1.9 GHz (Socket478, 400 FSB, L2 cache:256KB)	ALL	ALL	
P4-2 GHz (Socket478, 400 FSB, L2 cache:256KB)	ALL	ALL	
P4-2.20 GHz (400 FSB, L2 cache:512KB)	ALL	ALL	
P4-2.26 GHz (533 FSB, L2 cache:512KB)	ALL	ALL	
P4-2.40 GHz (400 FSB, L2 cache:512KB)	ALL	ALL	
P4-2.40B GHz (533 FSB, L2 cache:512KB)	ALL	ALL	
P4-2.50 GHz (400 FSB, L2 cache:512KB)	ALL	ALL	
P4-2.53 GHz (533 FSB, L2 cache:512KB)	ALL	ALL	
P4-2.60 GHz (400 FSB, L2 cache:512KB)	ALL	ALL	
P4-2.66 GHz (533 FSB, L2 cache:512KB)	ALL	ALL	

ALL

# P4SGX-MX

400 FSB, L2 cache:512KB)



P4-3.06 GHz (533 FSB, L2 cache:512KB, HT, C1/D1)

ALL

ALL



does not support HyperThreading

## Shop and Learn

- Mobile
- Phones
- Accessories
- Laptops
- For Home
- For Work
- For Creators
- For Students
- For Gaming
- Accessories
- Displays / Desktops
- Monitors
- Projectors
- All-in-One PCs
- Tower PCs
- Gaming Tower PCs
- Mini PCs
- Workstations
- Accessories
- Motherboards / Components**
- Motherboards
- Graphics Cards
- Gaming Cases
- Cooling
- Power Supply Units
- Sound Cards
- Optical Drives
- Data Storage
- External Graphics Docks
- Networking / IoT / Servers**
- WiFi Routers
- Whole Home Mesh WiFi System
- Wired Networking
- Intelligent Robots
- AIoT & Industrial Solutions
- Servers
- Smart Home
- Accessories**
- Keyboards
- Mice and Mouse Pads
- Headsets and Audio
- Streaming Kits
- Apparel Bags and Gear
- Cases and Protection
- Adapters and Chargers
- Docks Dongles and Cable
- Power Banks
- Controller
- Gimbal
- Display Accessories

## Learn More

- Asus Design Center
- ASUSPRO
- Automotive Solutions
- Support**
- Check Repair Status
- Find Service Locations
- Product Registration
- Email Us
- Call Us
- Security Advisory
- ASUS Support Videos
- MyASUS

## About Us

- About ASUS
- News
- Investor Relations
- About CSR for global
- Press Room
- ASUSTOR Inc.
- ASUS Cloud Corporation
- UniMax Electronics Inc.

## Community

