

[Corporate](#)
[About FIC](#)
[Contacts](#)

[What's New](#)
[Press Releases](#)
[Shows](#)
[Reviews &](#)
[Reports](#)

[Products](#)
[Mainboards](#)
[Systems](#)
[Portables](#)
[1stGrafx Series](#)
[Communications](#)
[Scanners](#)

[Tech Support](#)
[Mainboards](#)
[Portables](#)
[1stGrafx Series](#)
[FAQ](#)
[Windows 95 FAQ](#)

[BIOS](#)
[BIOS/Drivers](#)
[Updates](#)
[Update](#)
[Instructions](#)

[Specialist](#)
[Services](#)
[GOLF](#)

[Marketplace](#)
[Spotlight of the](#)
[Month](#)
[Distributor List](#)

[FIC Publications](#)
[LEO Outlook](#)
[FIC Focus](#)

[FYI@FIC](#)
[Newsletter](#)
[Subscribe](#)

[Download](#)
[User](#)
[Manuals](#)



PA-2100 Mainboard



Click [here](#) to view the PA-2100 product brochure.
(This may take a while - 269KB)

Features

- **Processor**
 - [Intel Pentium®](#) 75~166MHz;
 - [AMD-K5™](#)/[Cyrix 6x86™](#)/[IBM 6x86™](#);
 - Optional 320-pin ZIF socket;
 - Voltage Regulator Module support;
 - Upgradable to P54CS/P54CT/P55T processors
- **Chipset**
 - VIA Apollo Plus Chipset
- **Cache**
 - Onboard 1MB Direct Map Write-back cache
- **Memory**
 - Up to 128MB RAM; 4 x 72-pin SIMM sockets;
 - EDO DRAM support
- **Expansion Slots**
 - 3 x 16-bit ISA and 4 x 32-pin PCI slots
- **I/O**
 - NS 332/334 + DS14185 Multi-I/O chipset;
 - 2 serial ports with 16550 UART/SIR;
 - 1 parallel port with ECP/EPP;
 - Optional PS/2 keyboard and PS/2 mouse
- **Onboard Sound**
 - Crystal CS 4232 16-bit sound chip;
 - Yamaha OPL3 FM synthesizer;
 - Optional wavetable connector
- **Built-in PCI Bus**
 - VIA VT82C576;
- **Master EIDE**
 - Built-in IDE and FDC interface



■ **Additional Features**

APM 1.1 support;
FLASH EPROM support;
Plug and Play ready;
VIA VT82C416 RTC;
Energy Star compliant

■ **Form Factor**

4-layer Baby AT; 8.6" x 13"