# DTK Computer China

Room 402, LanGuang Building, No. 56, Zhenhua Road, Shenzhen, China


TEL:+86-755-3217870, 3217874, 3213586 FAX:+86-755-3243290 Web site: http://www.dtk.com.cn Email: sales@dtk.com.cn



# **PFM-11I**

# Intel 845G Socket 478 Micro-ATX Motherboard

PFM-11I is a high-performance green Intel Pentium 4 motherboard. The system core logic is based on Intel 845G Chipsets. It is integrated with Realtek RTL8100B Ethernet controller and Realtek ALC650 AC'97 codec for Software Audio.



# **SPECIFICATION**

#### CPU:

- Support Intel Socket 478 Pentium 4 processor
- 400MHz Quad-pumped Front Side Bus

#### **Chipset:**

- Intel 845G + ICH4 chipsets
- Realtek ALC650 AC'97 codec
- Winbond 83627HF LPC controller
- Realtek RTL8100B Ethernet controller

# **Main Memory:**

- •Two 184-pin DIMM sockets
- Support DDR200/266 SDRAM up to 2GB

#### VGA:

- Integrated Graphics controller in 845G GMCH
- Support 3D/2D enhancements
- Support AGP8X bandwidth including AGP4X slot.
  Max. Bandwidth 1GB/sec

### Audio:

- AC-Link with AC'97 2.2 compliant
- Software Audio with Realtek ALC650 AC'97 codec

#### Ethernet:

- Onboard Realtek RTL8100B Ethernet controller
- Full-Duplex supported
- Intel PXE supported

#### **System BIOS:**

- Award BIOS with 2MB/4MB Firmware Hub
- ACPI/PnP supported

# I/O Interface (ICH4):

- Two enhanced PCI IDE channels which support up to 4 IDE devices with ATA-100 transfers up to 100MB/sec
- Double Deck downstream USB 2.0 ports
- 2X5 pin header USB 2.0 ports

# I/O Interface (W83627HF):

- 2 COM ports & 1 Printer port
- 1 FDC supports 1.2M/1.44M/2.88M FDD
- PS/2 mouse and keyboard connectors
- IrDA 1.0/FIR support

### **H/W Monitoring**

- CPU/System fan revolution detect
- CPU/System temperature detect
- CPU overheat shutdown detect
- System voltage detect (Vcore, Vcc3, Vcc, +12V)

# **Other Features**

- Support Wake-On-LAN (WOL)
- Supports Internal / External Modem Ring On
- 2 cooling fan connectors

# **Expansion Slots:**

- 3 PCI slots
- •1 AGP4X slot

#### Form Factor:

ullet Micro-ATX @ 244 mm (L)  $\times$  244 mm (W), 4 Layers