# DTK Computer China Room 402, LanGuang Building, No. 56, Zhenhua Road,

Shenzhen, China TEL:+86-755-3217870, 3217874, 3213586 FAX:+86-755-3243290 Web site: http://www.dtk.com.cn Email: sales@dtk.com.cn



# PHM-23V

# VIA Apollo KT333 Socket-A ATX Motherboard

PHM-23V is a high-performance AMD K7 motherboard. The system core logic is based on VIA Apollo KT333 Chipsets. VT8367 North Bridge supports PC2700/2100/1600 DDR DRAM. VT8233A V-Link south bridge supports DMA ATA33/66/100/133. PHM-23V is integrated with NEC USB 2.0 controller and C-Media 6-CH-MX Audio controller.



# **SPECIFICATION**

#### CPU:

• Support AMD Socket A Athlon/Duron processor

## Chipset:

- VIA Apollo KT333 chipsets
- Winbond W83627HF LPC controller
- C-Media CMI8738/PCI-6CH-MX Audio controller
- •NEC D720100AGM USB 2.0 controller

## Main Memory:

- •3×184pin DDR DIMM slots
- Support PC2700/2100/1600 DDR DRAM
- Maximum Size 3GB

#### **Other Features**

- Support Wake-On-LAN (WOL)
- Suspend-To-RAM (STR)
- Supports Internal / External Modem Ring On
- •4 cooling fan connectors

#### Audio:

- Onboard C-Media CMI8738/PCI-6CH-MX Audio controller
- Support 4.1/5.1 speakers and DirectSound 3D

## USB2.0

- •NEC D720100AGM single chip
- Support 480 megabits per second (Mbits/s)
- Provide tow USB 2.0 fully compliant cable ports

#### LPC I/O:

- Winbond W83627HF chip
- Two enhanced PCI IDE channels which support up to 4 IDE devices with ATA-100 transfers up to 100MB/sec
- 2 COM ports & 1 Printer port
- One FDC supports 1.2M/1.44M/2.88M FDD
- Double desk USB 2.0 ports
- PS/2 mouse and keyboard connectors
- IrDA 1.0/FIR support

#### System BIOS:

- Award BIOS with 2MB/4MB EEPROM
- ACPI/PnP supported

#### **Expansion Slots:**

- •5 PCI slots
- •1 AGP4X slot

#### Form Factor:

•ATX form factor, 30.5cm × 24.5cm