

DTK Computers

Technical Information Sheet for PIM-TB-08-Z
S=shorted, 0=open DIP switch 1=on 0=off

SW1:Coprocessor SW1:1,3 & 4
 2 Function Not used
 1 Disabled
 0 Enabled

SW1:Display Select SW1:Floppys Installed
 5 6 Display type 7 8 Number
 1 1 EGA 1 1 One drive
 1 0 CGA (80x25) 0 1 Two drives
 0 1 CGA (40x25) 1 0 Three drives
 0 0 Monochrome 0 0 Four drives

JP3:Keyboard Lock JP1:Speaker
 S Unlocked <1> +5VDC
 0 Locked <2> Data out

JP5:Turbo LED & Turbo LED JP4:Reset Connector
 <1> Turbo Positive Lead S Reset
 <2> Turbo Negative Lead 0 Normal

 JP6:Hardware Turbo Switch
 S Turbo
 0 Normal

RAM Type

Memory Size	RAM Type Bank 0	Bank 1	Bank 2	Bank 3
256k	41256x9	none	none	none
512k	41256x9	41256x9	none	none
576K	41256X9	41256X9	4464X2 & 4164X1	none
640k	41256x9	41256x9	4464x2 & 4164x1	4464x2 & 4164x1

P1:Power Connector
 <1> Power Good <7> Ground
 <2> Not used <8> Ground
 <3> +12 VDC <9> -5 VDC
 <4> -12 VDC <10> +5 VDC
 <5> Ground <11> +5 VDC
 <6> Ground <12> +5 VDC