

# **PRM-0077I**

High Performance

Dual Pentium II

AGP/PCI Mainboard

**User's Guide**



Edition 1.10

© 1998 DTK Computer, Inc.

P/N: 155100-8617






---

## WARNING

For the system to operate normally, please make sure J11 of the mainboard is set as below. Refer to Fig. 3 in this manual for the location J11.



If J11 is shorted to 1-2, no CMOS data can be retained.

## CAUTION

The motherboard is an electrostatic sensitive device. Don't open or handle except at a static-free workstation.

## POWER OFF

It needs to hold the power switch 4 seconds to turn off the power.

Windows, MS-DOS, and MS Word are trademarks of Microsoft Corporation.

Novell, Netware are trademarks of Novell, Inc.

Lotus, 1-2-3, and Symphony are trademarks of Lotus Development Corporation.

PC, AT, PC-DOS, OS/2 and Presentation Manager are trademarks of IBM Corporation.

UNIX is the trademark of AT&T.

Intel i82440LX and Pentium II are registered trademark of Intel Corporation.

All other brand and product names are trademarks or registered trademarks of their respective companies.

The information presented in this publication has been carefully checked for reliability; however, no responsibility is assumed for inaccuracies, whereas, specification is subjected to change without notice.

---

# CONTENTS

<b>CHAPTER 1</b>	<b>INTRODUCTION</b>	<b>1</b>
<b>CHAPTER 2</b>	<b>JUMPER SETTINGS</b>	<b>5</b>
2.1	JUMPERS PRESENTATION	5
2.2	GRAPHICAL DESCRIPTION OF JUMPER SETTINGS	6
2.3	CPU SPEED	7
2.4	J11 - CLEAR CMOS DATA	7
2.5	MEMORY CONFIGUARTION	8
<b>CHAPTER 3</b>	<b>CONNECTOR CONFIGURATION</b>	<b>9</b>
3.1	PS1 - ATX POWER SUPPLY CONNECTOR	10
3.2	U28, U29 - SLOT 1 FOR PENTIUM II CPU	10
3.3	FAN1, FAN2 - CPU FAN CONNECTOR	10
3.4	J1 - POWER ON/OFF AFTER POWER FAILURE	11
3.5	J2 - IrDA CONNECTOR	11
3.6	J3 - SCSI CONNECTOR	11
3.7	J4 - ULTRA WIDE SCSI CONNECTOR	11
3.8	J6 - HDD LED	12
3.9	J7 - KEYLOCK AND POWER LED	12
3.10	J8 - POWER ON/OFF SWITCH	12
3.11	J9 - SPEAKER	12
3.12	J10 - RESET	13
3.13	J13 - FLOPPY DRIVE CONTROLLER	13
3.14	J14, J15 - PRIMARY/SECONDARY IDE CONNECTORS	13
3.15	JP5 - WAKE ON LAN CONNECTOR	13
3.16	PS/2 KEYBOARD CONNECTOR	14
3.17	PS/2 MOUSE CONNECTOR	14
3.18	UNIVERSAL SERIAL BUS PORT 0 & 1	14
3.19	SERIAL PORT COM1 & COM2	14
3.20	PARALLEL PORT CONNECTOR	14
3.21	RETENTION MECHANISM KITS INSTALLATION GUIDE	15
<b>CHAPTER 4</b>	<b>AWARD BIOS SETUP GUIDE</b>	<b>19</b>
4.1	AWARD BIOS SETUP	19
4.2	STANDARD CMOS SETUP	21
4.3	BIOS FEATURES SETUP	22
4.4	CHIPSET FEATURES SETUP	25
4.5	POWER MANAGEMENT SETUP MENU	27
4.6	PCI CONFIGURATION	30
4.7	INTEGRATED PERIPHERALS SETUP MENU	32
4.8	LOAD SETUP DEFAULTS MENU	34
4.9	SUPERVISOR PASSWORD	34
4.10	USER PASSWORD	34

---

4.11	IDE HDD AUTO DETECTION	35
4.12	SAVE & EXIT SETUP MENU	35
4.13	EXIT WITHOUT SAVING MENU	35
<b>CHAPTER 5</b>	<b>FLASH AND DMI UTILITY</b>	<b>37</b>
5.1	AWARD FLASH UTILITY	37
5.2	DESKTOP MANAGEMENT INTERFACE (DMI) OVERVIEW	39
<b>APPENDIX A</b>	<b>QUICK GUIDE</b>	<b>43</b>



---

# CHAPTER 1

# INTRODUCTION

## Preface

The motherboard is a 4 layer, ATX form factor high performance Dual Pentium II AGP/PCI mainboard. It includes Intel i82440LX system chipset, Winbond W83977TF Super I/O controller and Adaptec AIC-7880 SCSI controller.

## Features

### Processor

- ?? Intel Dual Pentium II series.
- ?? The mainboard can run with following speeds:  
233, 266, 300 and 333MHz

### Chipset

- ?? Intel i82443LX (PCI A.G.P. Controller)
- ?? Intel 82371AB (PCI ISA IDE Xcelerator)
- ?? Winbond W83977TF (Super I/O Controller)
- ?? Adaptec AIC-7880 (SCSI Controller)

### Main Memory

- ?? Memory configurations up to 512MB SDRAM/EDO.
- ?? DIMM socket for SDRAM (3.3V unbuffered).
- ?? Support both Synchronous DRAM and Extended Data Output (EDO) Mode DRAM Modules.
- ?? ECC Function ensure data correction and integrity.

### Multi I/O

- ?? On board Multi-I/O supports two serial, one parallel ports and floppy drive controller.
- ?? Serial ports are 16550 Fast UART compatible.
- ?? Parallel port has EPP and ECP capabilities.
- ?? PS/2 keyboard and PS/2 mouse connector is provided.
- ?? IrDA supported.
- ?? USB supported.

### Accelerated Graphics Port (AGP) Interface

- ?? A.G.P. specification compliant
- ?? A.G.P. 66/133MHz devices supported

### PCI IDE

- ?? On board supports PCI Master IDE Controller, two connectors support up to four IDE devices such as HDD, CD ROM drive and Tape Back-up drives, etc.
- ?? PCI Master IDE controller supports PIO Mode 3 and 4 devices, I/O data transfer rate can be up to 16.6MB/s.
- ?? Ultra DMA Mode supported. Transfer rate can be up to 33MB/s.

## **Chapter 1**

---

### **PCI SCSI**

- ?? Support Double Speed SCSI operation up to 4Mbytes/sec.
- ?? PCI Bus Master for data transfer.
- ?? 8 bit, 16 bit SCSI Bus support.

### **System BIOS**

- ?? Award BIOS (128KB Flash EPROM).

### **Slots**

- ?? One AGP slot
- ?? Four PCI slots (1 shared)
- ?? Three ISA slots(1 shared)

### **Form Factor**

- ?? Full ATX Size (305mm x 244mm) 4 Layer






Fig. 1 Key Components of the Mainboard



---

## CHAPTER 2

## JUMPER SETTINGS

### 2.1 JUMPERS PRESENTATION



Pins 1 and 2 are shorted with a jumper cap.



Pins 2 and 3 are shorted with a jumper cap.



The jumper is shorted when the jumper cap is placed over the two pins of the jumper.



The jumper is open when the jumper cap is removed from jumper.

#### Jumpers Convention

Different color of jumper caps (mini-jumpers) are used on the board to represent different usage of the jumpers:

Red: CPU Clock setting

Black: Other

## 2.2 GRAPHICAL DESCRIPTION OF JUMPER SETTINGS




Fig. 2 Jumper Location of the mainboard

### 2.3 CPU SPEED



The table below summaries the CPU frequency and settings of each jumper of the motherboard.

CPU Type	Freq.	Ratio	Bus Freq.	Rating Setting
Pentium II	233MHz	3.5x	66MHz	JP8: 1-2 open 3-4 open 5-6 close
Pentium II	266MHz	4.0x		JP8: 1-2 close 3-4 close 5-6 open
Pentium II	300MHz	4.5x		JP8: 1-2 open 3-4 close 5-6 open
Pentium II	333MHz	5.0x		JP8: 1-2 close 3-4 open 5-6 open

**Table 1: Jumper Setting**

### 2.4 J11 - CLEAR CMOS DATA

J11 is used to clear the content of the CMOS Data in the RTC (build in PIIX4 chip).

J11	Description
 1	Clear CMOS Data
 1	Normal

**Table 2: Clear CMOS Data**

## 2.5 MEMORY CONFIGUARTION

The mainboard lets user upgrade system memory via DIMM sockets on the mainboard. On board memory is located in eight banks: Bank 0 - 7. Four DIMM sockets are provided for EDO DRAM or Synchronous DRAM. Table 4 provide the typical memory configurations supported by the mainboard.

<b>Bank 0/1 (DIMM1)</b>	<b>Bank 2/3 (DIMM2)</b>	<b>Bank 4/5 (DIMM3)</b>	<b>Bank 6/7 (DIMM4)</b>
Installed	None	None	None
None	Installed	None	None
None	None	Installed	None
None	None	None	Installed
Installed	Installed	None	None
Installed	None	Installed	None
Installed	None	None	Installed
None	Installed	Installed	None
None	Installed	None	Installed
None	None	Installed	Installed
Installed	Installed	Installed	None
Installed	Installed	None	Installed
Installed	None	Installed	Installed
None	Installed	Installed	Installed
Installed	Installed	Installed	Installed

**Table 3**


The maximum memory size is up to 512MB (SDRAM/EDO). The size of each DIMM can be 8MB, 16MB, 32MB, 64MB or 128MB.

---

## CHAPTER 3

## CONNECTOR CONFIGURATION

Once the mainboard has been fastened into system case, the next step is to connect the internal cables. The internal cables are wire leads with plastic female connectors that attach to the connectors. The mainboard connectors have varying numbers of pins and are the points of contact between the mainboard and other parts of the computer.



**Fig 3 Connector Location**

### 3.1 PS1 - ATX POWER SUPPLY CONNECTOR




Fig. 4 ATX Power Supply Connector

### 3.2 U28, U29 - SLOT 1 FOR PENTIUM II CPU

U27 and U28 are the slots for Pentium II CPU.



Fig. 5 Slot 1 for Pentium CPU

### 3.3 FAN1, FAN2 - CPU FAN CONNECTOR

FAN1 & FAN2 are three pin connectors, which are used to connect with the CPU Fan Power cable.



### 3.4 J1 – POWER ON/OFF AFTER POWER FAILURE

This jumper sets the power of the system after the main power has failed then recovered

J1	System After Power Failure
ON	ON
OFF	OFF

Table 4

### 3.5 J2 - IrDA CONNECTOR

J2 is a IrDA connector that use UART2 as interface of IrDA Infrared and HP SIR.



Fig. 6 IrDA Connector

### 3.6 J3 - SCSI CONNECTOR

J3 is a 50 pin connector for a SCSI device.

### 3.7 J4 - ULTRA WIDE SCSI CONNECTOR

J4 is a high density 68 pin connector for a wide SCSI device.

### 3.8 J6 - HDD LED

J6 is usually connected to a HDD LED on front of the system case. If the HDD is in operation, the indicator lights during operation.



Fig. 7 HDD LED

### 3.9 J7 - KEYLOCK AND POWER LED




Fig. 8 Power LED

### 3.10 J8 - POWER ON/OFF SWITCH

It is used to switch on or off the ATX power supply. The power is turned on by short the power switch once. It needs to hold the power switch about 4 seconds to turn it off when it has not start to display.

### 3.11 J9 - SPEAKER

J9 is a four pins connector, which is used to connect the system speaker.



Fig. 9 Speaker

### **3.12 J10 - RESET**

Attach the Reset switch cable to this connector. The Reset switch restarts the system.

### **3.13 J13 - FLOPPY DRIVE CONTROLLER**


This connector supports the floppy drive ribbon cable. After connecting the single end to the board, connect the two plugs on the other end to the floppy drive.

### **3.14 J14, J15 - PRIMARY/SECONDARY IDE CONNECTORS**


These connectors support the provided IDE hard disk ribbon cable. After connecting the single end to the board, connect the two plugs on the other end to your hard disk or other device.

### **3.15 JP5 - WAKE ON LAN CONNECTOR**

JP5 is a 3-pin connector as interface of LAN card for wake up on LAN purpose.



**Fig. 10 Wake On LAN Connector**



**Fig. 11 I/O Connector**

### **3.16 PS/2 KEYBOARD CONNECTOR**

This connector is a six-pin female mini DIN connector using a PS/2 plug. If a standard AT size keyboard plugs, you may use the DIN to mini DIN adaptor.

### **3.17 PS/2 MOUSE CONNECTOR**

This connector is a six-pin female mini DIN connector using a PS/2 plug. Plug the jack on the PS/2 keyboard cable into this connector.

### **3.18 UNIVERSAL SERIAL BUS PORT 0 & 1**

These connectors are two four pin female sockets which are available for connecting USB device.

### **3.19 SERIAL PORT COM1 & COM2**

This is a D-Type 9 pin male connector for pointing devices or other serial devices.


### **3.20 PARALLEL PORT CONNECTOR**

This is a D-Type 25 pin female connector.

### 3.21 RETENTION MECHANISM KITS INSTALLATION GUIDE


Retention Mechanism Kits includes following components:

1. Retention mechanism Assembly




**Fig. 12**

2. Retention Mechanism Attach Mount




**Fig. 13**

3. Heatsink Top Support




**Fig. 14**

4. Heatsink Support Base



**Fig. 15**


Before the installation of RM Kits find the six holes on the motherboard for RM installation. The hole position and usage is as following:




**Fig. 16**

**Installation Guide**

1. Mount the two RM Attach Mounts onto the motherboard from bottom side. These mounts will be used to attach the RM Assembly.
2. Put the RM Assembly on the Slot 1 and use the four screws to fix RM Assembly to the RM Attach Mount.
3. Install the Heatsink Support Base onto the motherboard, insert the two plastic nail to the hole in the Heatsink Support Base as following diagram:

**Fig. 17**

4. Insert the Heatsink Top Support to the Pentium II Heatsink and the Heatsink Support Base as the following diagram:

**Fig. 18**





---

## CHAPTER 4

## AWARD BIOS SETUP GUIDE

This following manual is specially provided for the BIOS supported system. After the configuration of the mainboard, and have assembled the components, user can turn on the completed system. At this point, run the software setup to ensure that the system information is correct.

The software setup of the system board is achieved through Basic Input-Output System (BIOS) programming. Use the BIOS setup program to tell the operating system what type of devices (such as disk drives) are connected to the system board.

The system setup is also called CMOS setup. Normally, users need to run system setup if either the hardware configuration is not identical with information contained in the CMOS RAM, or the CMOS RAM has lost power.

### 4.1 AWARD BIOS SETUP

The setup program provided with the mainboard is the Award BIOS from Award Software, Inc. Enter the AWARD Setup program's Main Menu as follows:

1. Turn on or reboot the system. After a series of diagnostic check, the following message appear:

**“Press DEL to enter SETUP”**

---

**Chapter 4**

2. Press the <DEL> key to enter the AWARD BIOS setup program and the following screen appears:

ROM PCI/ISA BIOS (2A69JD1A)  
CMOS SETUP UTILITY  
AWARD SOFTWARE, INC.

STANDARD CMOS SETUP	INTEGRATED PERIPHERALS
BIOS FEATURES SETUP	SUPERVISOR PASSWORD
CHIPSET FEATURES SETUP	USER PASSWORD
POWER MANAGEMENT SETUP	IDE HDD AUTO DETECTION
PNP/PCI CONFIGURATION	SAVE & EXIT SETUP
LOAD SETUP DEFAULTS	EXIT WITHOUT SAVING
Esc : Quit	? ? ? ? : Select Item
F10 : Save & Exit Setup	(Shift)F2 : Change Color
Time, Data, Hard Disk Type...	

**Fig. 19**

3. Choose an option and press <Enter>. Modify the system parameters to reflect the options installed in the system. (see the following sections for more information).
4. Press <ESC> at anytime to return to the Main Menu.
5. In the Main Menu, choose “SAVE AND EXIT SETUP” to save change and reboot the system. Choosing “EXIT WITHOUT SAVING” to ignore all changes and exists the program.

## 4.2 STANDARD CMOS SETUP

ROM PCI/ISA BIOS (2A69JD1A)  
STANDARD CMOS SETUP  
AWARD SOFTWARE, INC.

Date (mm:dd:yy) : Wed, May 21 1997									
Time (hh:mm:ss) : 20 : 27 : 55									
<b>HARD DISKS</b>									
<b>TYPE</b>	<b>SIZE CYLS HEAD PRECOMP LANDZ SECTOR MODE</b>								
Primary Master : Auto	0 0 0 0 0 0 AUTO								
Primary Slave : None	0 0 0 0 0 0 -----								
Secondary Master : None	0 0 0 0 0 0 -----								
Secondary Slave : None	0 0 0 0 0 0 -----								
Drive A : 1.44M , 3.5in.	<table border="1"> <tr> <td>Base Memory:</td> <td>0K</td> </tr> <tr> <td>Extended Memory:</td> <td>0K</td> </tr> <tr> <td><u>Other Memory:</u></td> <td><u>512K</u></td> </tr> <tr> <td>Total Memory:</td> <td>512K</td> </tr> </table>	Base Memory:	0K	Extended Memory:	0K	<u>Other Memory:</u>	<u>512K</u>	Total Memory:	512K
Base Memory:		0K							
Extended Memory:		0K							
<u>Other Memory:</u>	<u>512K</u>								
Total Memory:	512K								
Drive B : None									
Floppy 3 Mode Support : Disabled									
Video : EGA/VGA									
Halt On : All Errors									
Esc : Quit	?? ? ? : Select Item								
F1 : Help	(Shift)F2 : Change Color								
	PU/PD/+/- : Modify								

**Fig. 20**

<b>Date(mm/dd/yy)</b>	Type the current date.
<b>Time(hh:mm:ss)</b>	Type the current time.
<b>Hard Disks</b>	Choose from the standard hard disk types 1 to 45. Type 47 is user definable. Type Auto is for auto detect the hard disk type.
<b>Drive A &amp; B</b>	Choose 360K, 5.25in.; 1.2M, 5.25in.; 720K, 3.5in.; 1.44M, 3.5in.; 2.88MB 3.5in. or None
<b>Video</b>	Choose EGA/VGA, CGA 40, CGA 80, or MONO,
<b>Halt On</b>	Choose All Errors; No Errors; All, But Keyboard; All, But Diskette or All, But Disk/Key
<b>Floppy 3 Mode Support</b>	Choose Enabled to allow floppy drive support 3 Mode.

### 4.3 BIOS FEATURES SETUP

ROM PCI/ISA BIOS (2A69JD1A)  
 BIOS FEATURES SETUP  
 AWARD SOFTWARE, INC.

Virus Warning	: Disabled	Video BIOS Shadow	: Disabled
CPU Internal Cache	: Enabled	C8000-CBFFF Shadow	: Disabled
External Cache	: Enabled	CC000-CFFFF Shadow	: Disabled
Quick Power On Self Test	: Disabled	D0000-D3FFF Shadow	: Disabled
Boot Sequence	: A,C,SCSI	D4000-D7FFF Shadow	: Disabled
Swap Floppy Drive	: Disabled	D8000-DBFFF Shadow	: Disabled
Boot Up Floppy Seek	: Enabled	DC000-DFFFF Shadow	: Disabled
Boot Up Numlock Status	: On		
Boot Up System Speed	: High		
Gate A20 Option	: Fast		
Typematic Rate Setting	: Disabled		
Typematic Rate (Chars/Sec)	: 6		
Typematic Delay (Msec)	: 250		
Security Option	: Setup		
PCI/VGA Palette Snoop	: Disabled		
Assign IRQ For VGA	: Disabled	ESC: Quit	? ? ? ? : Select Item
MPS Version Control For OS	: 1.4	F1: Help	PU/PD/+/-: Modify
OS Select For DRAM > 64MB	: Non-OS2	F5: Old Values	(Shift)F2: Color
HDD S.M.A.R.T. capability	: Disabled	F7: Load Setup Defaults	
Report No FDD For Win95	: No		

Fig. 21 BIOS Setup Defaults

**A short description of the screen items follows:**

**Virus Warning:** When enabled, you receive a warning message if a program (specifically, a virus) attempts to write to the boot sector or the partition table of the hard disk drive. You should then run an anti-virus program. The default is Disabled.

**CPU Internal Cache:** Choose Enabled or Disabled. This option lets user choose whether to use CPU internal cache memory. The default is Enabled.

**External Cache:** Choose Enabled or Disabled. This option lets user choose whether to use secondary cache memory. The default is Enabled.

**Quick Power On Self Test:** Choose Enabled or Disabled. This option let the POST sequence runs longer for through tests.

**Boot Sequence:** With the default setting the BIOS first attempts to boot from drive A: and then, if unsuccessful, from hard disk C:. User can select other boot up sequence. Available sequences are "A,C,SCSI", "C,A,SCSI", "C,CDROM,A", "CDROM,C,A", "D,A,SCSI", "E,A,SCSI",

“F,A,SCSI”, “SCSI,A,C”, “SCSI,C,A”, “C only”, “LS120,C”.

## Chapter 4

---

**Swap Floppy Drive:** Choose Enabled or Disabled. This option lets end users to change the Drive A: or B: to others.

**Boot Up NumLock Status:** Choose On or Off. On puts numeric keypad in Num Lock mode at boot-up. Off puts numeric keypad in arrow key mode at boot-up.

**Boot Up System Speed:** Choose High or Low. Set the CPU timing at Boot Up, the default is high.

**Gate A20 Option:** Choose Fast (chipset handled) or Normal (keyboard handled). The gate A20 is a device used to address memory above 1Mbytes. Initially, the gate A20 was handled via a pin on the keyboard. Today, while keyboards still provide this support, it is more common, and much faster, for the system chipset to provide support for gate A20.

**Typematic Rate Setting:** Choose Enabled or Disabled. Enabled will determines the typematic rate defined by following two options.

**Typematic Rate:** The number selected 6,8,10... indicates how fast the number of characters can response in one second.

**Typematic Delay (Msec):** The number selected indicates the time period between two identical keys appear.

**Security Option:** Choose Setup or System. If system is selected, the password should be set.

**PCI/VGA Palette Snoop:** Select Disabled or Enabled. If Enabled the MPEG Card can synchronised with PCI/VGA.

**Assign IRQ For VGA:** Choose Enabled or Disabled. Enabled will assign and IRQ to Graphic Controller.

**OS Select For DRAM > 64MB:** Select Disabled or Enabled. If the system memory is larger than 64MB and running OS/2, please enable this item. However, if it use other operating system, please disable this feature. Furthermore, if the system memory is less than 64MB, the BIOS will ignore this function.

**HDD S.M.A.R.T. capability:** Choose Enabled or Disabled. Enabled will support the hard driver S.M.A.R.T. feature (Self-Monitoring, Analysis and Reporting Technology).

**Video BIOS Shadow:** ROM Shadow copies Video BIOS code from slower ROM to faster RAM. Video BIOS can then execute from RAM.

**C8000-DFFFF Shadow:** If enabled and BIOS is present in this segment, then the BIOS is shadowed.

## 4.4 CHIPSET FEATURES SETUP

The Advanced Chipset Setup option is used to change the values of the chipset registers. These registers control most of the system options in the computer.

*Note: Change these Settings only if user is familiar with the Chipset.*

ROM PCI/ISA BIOS (2A69JD1A)  
CHIPSET FEATURES SETUP  
AWARD SOFTWARE, INC.

Auto Configuration	: Enabled	SDRAM CAS Latency Time	: 3
DRAM Speed Selection	: 60ns	Current System Temp.	: 27°C/82°F
MA Wait State	: Slow	Current CPUFAN1 Speed	: 4800RPM
EDO RAS# To CAS# Delay	: 3	Current CPUFAN2 Speed	: 4800RPM
EDO RAS# Precharge Time	: 4		
EDO DRAM Read Burst	: x222		
EDO DRAM Write Burst	: x333	Vcore	: 2.76      2.5 (V) : 2.48
DRAM Data Integrity Mode	: Non-ECC	3.4 (V)	: 3.38      5.0 (V) : 5.04
CPU-To-PCI IDE Posting	: Enabled	12 (V)	: 11.82    -12 (V) : -11.78
System BIOS Cacheable	: Disabled	-5 (V)	: -4.87
Video BIOS Cacheable	: Enabled		
Video RAM Cacheable	: Enabled		
8 Bit I/O Recovery Time	: 1		
16 Bit I/O Recovery Time	: 1		
Memory Hole At 15M-16M	: Disabled		
Passive Release	: Enabled		
Delayed Transaction	: Enabled	ESC: Quit	? ? ? ? : Select Item
AGP Aperture Size (MB)	: 64	F1: Help	PU/PD/+/-: Modify
SDRAM RAS-to-CAS Delay	: Slow	F5: Old Values	(Shift)F2: Color
SDRAM RAS Precharge Time	: Slow	F7: Load Setup Defaults	

Fig. 22

**A short description of the screen items follows:**

**Auto Configuration:** When Auto Configuration is Enabled, BIOS will sets the CPU Clock according to CPU speed. Otherwise, set it manually.

**DRAM Speed Selection:** Choose 60ns or 70ns according to the DRAM SIMM Module on the motherboard.

**MA Wait State:** When this option is slow. One additional wait state is inserted before the assertion of first MA and CAS#/RAS# during DRAM read or write leadoff cycles. The affects pages hit, row miss and page miss cases. The settings are Slow or Fast.

## Chapter 4

---

**EDO RAS# To CAS# Delay:** When EDO DRAM is refreshed, both rows and columns are addressed separately. This setting item select the delay cycles between the assertion of RAS# and CAS#.

**EDO DRAM Read Burst:** This sets the timing for burst mode reads from DRAM. The options are x222 or x333.

**EDO DRAM Write Burst:** This sets the timings for burst write to DRAM. The options are x222 or x333.

**System BIOS Cacheable:** Choose Enabled or Disabled. “Enabled” allows system BIOS be cacheable.

**Video BIOS Cacheable:** Choose Enabled or Disabled. “Enabled” allows video BIOS be cacheable.

**Video RAM Cacheable:** Choose Enabled or Disabled. “Enabled” allows video RAM to be cacheable.

**8 Bit I/O Recovery Time:** This option specifies the length of the delay (in SYSCLKs) inserted between consecutive 8 bit I/O operations. The settings are 1,2,3,4,5,6,7,8 or N/A. The default setting is 1.

**16 Bit I/O Recovery Time:** This option specifies the length of the delay (in SYSCLKs) inserted between consecutive 16 bit I/O operations. The settings are 1,2,3,4,5,6,7,8 or N/A. The default setting is 1.

**Memory Hole At 15M-16M:** Choose Enabled or Disabled. “Enabled” allows some linear VGA cards to run larger frame port, or it can be reserved for some operating system.

**SDRAM RAS-To-CAS Delay:** When this option is slow, a delay time between the assertion of SDRAM RAS# and CAS#. The settings are Fast or Slow.

**Current System Temp.:** This item will show the temperature of the system board.

**Current CPUFAN1 Speed:** This item will show the rotate speed per minute of the CPUFAN1.

**Current CPUFAN2 Speed:** This item will show the rotate speed per minute of the CPUFAN2.

**Vcore/2.5(V)/3.4(V)/5.0(V)/12(V)/-12(V)/-5(V):** These items show the different voltage of the system board.



## 4.5 POWER MANAGEMENT SETUP MENU

The Power Management Setup option is used to change the values of the chipset registers for system power management functions.

ROM PCI/ISA BIOS (2A69JD1A)	
POWER MANAGEMENT SETUP	
AWARD SOFTWARE, INC.	
Power Management	: User Define
PM Control by APM	: Yes
Video Off Method	: V/H SYNC + Blank
Video off After	: Suspend
MODEM Use IRQ	: 3
Suspend Mode	: Disabled
HDD Power Down	: Disabled
HDD Power When Suspend	: Enabled
VGA Active Monitor	: Enabled
Soft-Off by PWR-BTTN	: Delay 4 sec.
CPUFAN Off In Suspend	: Enabled
Resume by Ring	: Enabled
IRQ 8 Break Suspend	: Disabled
** Reload Global Timer Events **	
IRQ [3-7,9-15], NMI	: Enabled
Primary IDE 0	: Disabled
Primary IDE 1	: Disabled
Secondary IDE 0	: Disabled
Secondary IDE 1	: Disabled
Floppy Disk	: Disabled
Serial Port	: Enabled
Parallel Port	: Disabled
ESC: Quit	? ? ? ? : Select Item
F1: Help	PU/PD/+/-: Modify
F5: Old Values	(Shift)F2: Color
F7: Load Setup Defaults	

Fig. 23

### A short description of the screen items follows:

**Power Management:** Available selection are “Disabled”, “User Define”, “Max Saving” and “Min Saving”:

“Disabled” will disable all the power saving functions.

“User Define” makes the time period waiting for Suspend Mode to be programmed.

“Max Saving” will set the time period waiting for Suspend Mode to be 20 seconds.

“Min Saving” will set the time period waiting for Suspend Mode to be 40 minutes.

**PM Control by APM:** Available options are “Yes” and “No”. To choose “Yes” to let the Power Management Function to be control by the MS APM software.

**Video Off Method:** Choose V/H SYNC+Blank, DPMS or Blank Screen. This is monitor Power Saving Method. V/H SYNC+Blank means turn off Vertical, Horizontal scanning and blank the screen. Blank Screen will blank the display screen. DPMS (Display Power Management System) can allow the System BIOS control the Display Card to turn off the Display.



**Video Off After:** As the system moves from lesser to greater power-saving modes. Select the mode in which you want the monitor to blank. The available options are “Standby”, “Suspend”, “Doze” and “NA”.

**MODEM Use IRQ:** Available options are 3,4,5,7,9,10,11 and NA. It is used to choose the interrupt line that the Modem is used. “NA” means not available.

**Suspend Mode:** To set the time period waiting for Suspend Mode when the Power Management function is set to “User Define”.

**HDD Power Down:** To select the time period will turn the HDD off. Accessing the HDD again will take a few seconds for HDD to spin up for operation.

**HDD Down When Suspend:** When Enabled, hard disk will be turn off if the system enter Suspend Mode.

**VGA Active Monitor:** When Enabled, any video activity restarts the global timer for Standby Mode.

**Soft-Off by PWR-BTTN:** Available options are “Instant-Off” and “Delay 4 sec.”. For “Instant-Off” option, the power of the system will be switched off at once when the power button is pressed for turn it off. For “Delay 4 sec.” Option, the power of the system will be switched off with 4 seconds later after the power button is pressed.

**CPUFAN Off In Suspend:** If the option is set to Enabled, the CPUFAN will stop when system is in suspend mode.

**Resume by Ring:** When Enabled the external modem ring in can wake up the system. (ATX power supply required)

**IRQ 8 Break Suspend:** You can select Enabled or Disabled monitoring of IRQ8 (the Real Time Clock) so it does not awaken the system from Suspend Mode.

**Reload Global Timer Event:** When Enabled, an event occurring on each device listed below restarts the global time for Standby Mode.

- IRQ[3-7,9-15], NMI
- Primary IDE 0
- Primary IDE 1
- Secondary IDE 0
- Secondary IDE 1
- Floppy Disk
- Serial Port
- Parallel Port

## 4.6 PCI CONFIGURATION

The PCI Configuration Setup option is used to configure the PCI add-on Cards on PCI Slots. Without proper setup the PCI Add-on Cards might not function properly.

ROM PCI/ISA BIOS (2A69JD1A)  
 PNP/PCI CONFIGURATION  
 AWARD SOFTWARE, INC.

PNP OS Installed	: No	PCI IDE IRQ Map To	: PCI-AUTO
Resources Controlled By	: Manual	Primary IDE INT#	: A
Reset Configuration Data	: Disabled	Secondary IDE INT#	: B
IRQ-3 assigned to	: Legacy ISA	Used MEM base addr	: C800
IRQ-4 assigned to	: Legacy ISA	Used MEM Length	: 8K
IRQ-5 assigned to	: PCI/ISA PnP		
IRQ-7 assigned to	: PCI/ISA PnP		
IRQ-9 assigned to	: PCI/ISA PnP		
IRQ-10 assigned to	: PCI/ISA PnP		
IRQ-11 assigned to	: PCI/ISA PnP		
IRQ-12 assigned to	: PCI/ISA PnP		
IRQ-14 assigned to	: PCI/ISA PnP		
IRQ-15 assigned to	: PCI/ISA PnP		
DMA-0 assigned to	: PCI/ISA PnP		
DMA-1 assigned to	: PCI/ISA PnP	ESC: Quit	? ? ? ? : Select Item
DMA-3 assigned to	: PCI/ISA PnP	F1: Help	PU/PD/+/-: Modify
DMA-5 assigned to	: PCI/ISA PnP	F5: Old Values	(Shift)F2: Color
DMA-6 assigned to	: PCI/ISA PnP	F7: Load Setup Defaults	
DMA-7 assigned to	: PCI/ISA PnP		

Fig. 24

*Note: Change these Settings only if user is familiar with the Chipset and all the PCI Add-on Cards functions.*

**A short description of the screen items follows:**

**PNP OS Installed:** Set this option to Yes if the operating system installed in the computer is Plug and Play-aware (e.g. Windows 95).

**Resources Controlled By:** The Award Plug and Play BIOS can automatically configure all the boot and Plug and Play compatible device. If you select Auto, all the interrupt (IRQ) and DMA assignment fields disappear, as the BIOS automatically assigns them.

**Reset Configuration Data:** If enable this option, the BIOS will clear and reset the ESCD after hardware reset.

**IRQ#/DMA# assigned to:** These items will be shown only when “Resources Controlled By” option is set the “Manual”. The available options are “Legacy ISA” and “PCI/ISA PnP”. If the option is set to “Legacy ISA”, the BIOS will never assign the specified IRQ/DMA resource to PCI or ISA PnP Devices. If “PCI/ISA PnP” is chosen, the BIOS will make the specified IRQ/DMA have a chance to be assigned to the PCI or ISA PnP devices.

**PCI IDE IRQ Map To:** Choose PCI-AUTO, PCI-SLOT1, PCI-SLOT2, PCI-SLOT3, ISA. The default setting is PCI-AUTO.

**Primary/Secondary IDE INT#:** Each PCI peripheral connection is capable of activating up to four interrupts: INT#A, INT#B, INT#C and INT#D. By default, a PCI connection is assigned INT#A. Assign INT#B has no meaning unless the peripheral device requires two interrupt services them just one.

**Used MEM Base Addr/Used MEM Length:** These items will be shown only when “Resources Controller By” option is set to “Manual”. They are used to reserve the memory space for the memory installed on the ISA card in the specified memory segment (such as some network card). The available options for “User Mem Base Addr” are “N/A”, “C800”, “CC00”, “D000”, “D400”, “D800” and “DC00”, which is used to select the base memory address of the ISA card used. With the “Used Mem Base Addr” is selected, the size of the memory installed on ISA card is chosen by “Used Mem Length”: “8K”, “16K”, “32K” or “64K”

## 4.7 INTEGRATED PERIPHERALS SETUP MENU

The Integrated Peripherals setup option is need to change the values of the I/O chipset registers for I/O functions.

ROM PCI/ISA BIOS (2A69JD1A)  
INTEGRATED PERIPHERALS  
AWARD SOFTWARE, INC.

IDE HDD Block Mode	: Enabled	Onboard Parallel Port	: 378/IRQ7
IDE Primary Master PIO	: Auto	Parallel Port Mode	: ECP+EPP
IDE Primary Slave PIO	: Auto	ECP Mode Use DMA	: 1
IDE Secondary Master PIO	: Auto	EPP Mode Select	: EPP1.9
IDE Secondary Slave PIO	: Auto		
IDE Primary Master UDMA	: Auto		
IDE Primary Slave UDMA	: Auto		
IDE Secondary Master UDMA	: Auto		
IDE Secondary Slave UDMA	: Auto		
On-Chip Primary IDE	: Enabled		
On-Chip Secondary IDE	: Enabled		
Onboard PCI SCSI Chip	: Enabled		
USB Keyboard Support	: Disabled		
Onboard FDD Controller	: Enabled		
Onboard Serial Port 1	: 3F8/IRQ4		
Onboard Serial Port 2	: 2F8/IRQ3		
UART Mode Select	: IrDA		
RxD, TxD Active	: Hi, Hi	ESC: Quit	? ? ? ? : Select Item
IR Transmittion delay	: Enabled	F1: Help	PU/PD/+/-: Modify
		F5: Old Values	(Shift)F2: Color
		F7: Load Setup Defaults	

Fig. 25

**A short description of the screen items follows:**

**IDE HDD Block Mode:** This allows your hard disk controller to use the fast block mode to transfer data to your hard disk drive.

**IDE Primary Master PIO/IDE Primary Slave PIO/IDE Secondary Master PIO/IDE Secondary Slave PIO:** Available selection are “Auto”, “Mode 0”, “Mode 1”, “Mode 2”, “Mode 3” and “Mode 4”. To choose “Auto”, the system BIOS will scan the IDE device and decide which mode of the device is . Otherwise the user should key in the mode of the device to the corresponding field.

*Some harddisks cannot work properly with its corresponding timing, please set a slower timing.*

**IDE Primary Master UDMA/IDE Primary Slave UDMA/IDE Secondary Master UDMA/IDE Secondary Slave UDMA:** Available selection are “Auto” or “Disabled”. To choose “Auto”, the system BIOS will scan the IDE device and decide Ultra DMA supported or not.

**On-Chip Primary/Secondary PCI IDE:** This item is used to set the onboard IDE controller. The settings are Primary, Secondary, Both or Disabled. The default setting is Both.

**Onboard SCSI Chip:** Select Enabled if your board contain a SCSI chip onboard.

**USB Keyboard Support:** Select Enabled if your system contains a Universal Serial Bus (USB) controller and you have a USB keyboard.

**Onboard FDD Controller:** Choose Enabled or Disabled. “Enabled” allows onboard Floppy Drive Controller to be functioned, otherwise the users should use other sources..

**Onboard Serial Port 1:** Choose Auto, Disabled, 3F8/IRQ4, 2F8/IRQ3, 3E8/IRQ4 and 2E8/IRQ3. While choosing proper I/O Address/IRQ, be sure not to cause Address conflict with other I/O devices. The default setting is 3F8/IRQ4.

**Onboard Serial Port 2:** Choose Auto, Disabled, 3F8/IRQ4, 2F8/IRQ3, 3E8/IRQ4 and 2E8/IRQ3. While choose proper I/O Address/IRQ, be sure not to cause Address conflict with other I/O devices. The default setting is 2F8/IRQ3.

**UART Mode Select:** Choose Normal, ASKIR (Amplitude Shift Keyed Infrared Port) or IrDA for serial Interface.

**RxD, TxD Active:** The available options are “Hi, Hi”, “Hi, Lo”, “Lo, Hi” and “Lo, Lo”. It is used to configure the logic level of Receive and Transmit signal in IrDA interface.

**IR Transmittion delay:** Choose Enabled for IrDA transmit delay.

**Onboard Parallel Port:** Choose None or with four different I/O Address and corresponding IRQx. While choosing proper I/O Address, be sure not to cause Address conflict with other I/O devices.

**Parallel Port Mode:** Choose SPP, ECP, EPP and ECP+EPP. Make proper selection with the attached printer port device.

**ECP Mode Use DMA:** Choose “1” or “3” to select the DMA channel used for the ECP device. This item is shown if the **Onboard Parallel Mode** is chosen as “ECP” or “ECP+EPP” option.

**EPP Mode Select:** Choose EPP1.7 or EPP1.9 for the EPP Mode.

## 4.8 LOAD SETUP DEFAULTS MENU

This Main Menu item uses the default setup values. Use this option as a diagnostic aid if the system behaves erratically. Choose this item and the following message appears:

**“Load SETUP Defaults (Y/N)? N”**

To use the Power-On defaults, change the prompt to “Y” and press <Enter>.

## 4.9 SUPERVISOR PASSWORD

Two level of password is supported. Depending on the setting of the “Security Option” in the “BIOS FEATURES SETUP”, the system BIOS will ask for password every time booting up the System or entering BIOS Setup. With the supervisor password, both the system booting and BIOS setup changing is allowed.

This main menu item lets the user to set up the Supervisor Password.

Change the password as follows:

1. Choose “PASSWORD SETTING” in the Main Menu and press <Enter>. The following message appears:

**“ENTER PASSWORD:”**

2. Enter the Password and press <Enter>. The following message appears:

**"CONFIRM PASSWORD:"**

*Important: Keep a safe record of the new password. If forget or lose the password, the only way to access the system is to disconnect the CMOS batteries and then re-enter the password.*

## 4.10 USER PASSWORD

With the user password, only booting up the system is accepted, but changing the BIOS setup is not allowed.



#### 4.11 IDE HDD AUTO DETECTION

When users can not find the Hard Disk information, it is very helpful to use this option.

1. Choose this item and press <Enter>.
2. After couple seconds, the screen will appear the Hard Disk information and following message:

**“SELECT PRIMARY MASTER OPTION(N=SKIP): N”**

3. Enter Y or N to confirm the acceptance then enter.
4. The process will repeat for Primary Slave, Secondary Master and Secondary Slave Hard Disks.

#### 4.12 SAVE & EXIT SETUP MENU

When you select this function, the following message will appear at the centre of the screen to assist you to Save data to CMOS and Exit the Setup.

**Save to CMOS and Exit (Y/N)?**

#### 4.13 EXIT WITHOUT SAVING MENU

When you select this function, the following message will appear at the centre of the screen to assist you to Abandon all Data and Exit Setup.

**Quit Without Saving (Y/N)?**



---

## CHAPTER 5

## FLASH AND DMI UTILITY

### 5.1 AWARD FLASH UTILITY

This section will provide instructions to guide you through updating your old BIOS. The file name we use to program here is *test.bin*, and the file name to save old BIOS is *2A59F000.OLD*. Please note that those file names are not absolute. They are only examples to let you have a more clear understanding of the updating process.

#### How to Begin

1. Please type "*awdflash*" and press the **ENTER** key to begin the updating process.
2. Once you enter, you will see a main menu displaying:

FLASH MEMORY WRITER V5.XX Copyright (C) 1996, Award Software, Inc.,	
For I430HX-2A59F000 Flash Type	DATE: 06/18/96
File Name to Program:	
Error Message:	

**Fig. 26**

3. Type the program name "*test.bin*", and then press the **ENTER** key.
4. At the bottom of the menu, you will be requested to answer:

***"Do You Want to Save BIOS (Y/N)?"***

If you do not wish to save the old BIOS:

5. Please type “N”, and then press the ENTER key.
6. Then you will be request to answer:

***“Are You Sure to Program?”***

7. Answer “N” if you do not want to program, and then it will exit.

To save the old BIOS:

8. Please respond “Y”, and then press the ENTER key.
9. Move the cursor to “File Name to Save:”
10. Type file name “**2A59F000.OLD**”, and then press the **ENTER**.  
(Your old BIOS will be saved in the file name you create. In this case, the old BIOS is saved in the file name, 2A59F000.OLD).
11. Then you will be requested to answer:

***“Are You Sure to Program (Y/N)?”***

12. Type “Y” to begin programming, and press the **ENTER** key.
13. When the programming is finished, the showing message will appear:

***“Programming Flash Memory - 1FF00 0K***

***Message: Please Power off or Reset System”***

14. Once you see the showing message “**Power Off or Reset System**”, please re-start your system.
15. When you power on the computer again, you will find your old BIOS has already been successfully updated.

**Warning**

Please note that Award Flash Utility cannot run under EMM386 or QEMM. Thus, when executing the command “**awdf**lash”, and error message will appear:

***“Error Message: Fail - Due to EMM386 or QEMM!”***

## 5.2 DESKTOP MANAGEMENT INTERFACE (DMI) OVERVIEW

This motherboard can support DMI within the BIOS level. DMI is able to auto-detect and record information pertinent to a computer's system such as the CPU type, CPU speed, and internal/external frequencies, and memory size. The onboard BIOS will detect as many system information as possible and store those collected information in a 4KB block in the motherboard's flash EPROM and allow the DMI to retrieve data from this database.

The DMI Configuration Utility (DMICFG.EXE) must be used in real mode in order for the program to run, the base memory must be at least 180K. Memory managers like HIMEM.SYS (required by windows) must not be installed. You can boot up from a system diskette without AUTOEXEC.BAT and CONFIG.SYS files, "REM" HIMEM.SYS in the CONFIG.SYS, or press <F5> during bootup to bypass your AUTOEXEC.BAT and CONFIG.SYS files.

### Using the DMI Configuration Utility

#### Edit DMI

```

Award DMI Configuration Utility V1.04a, Copyright Award Software Inc. 1996
[Edit DMI] [Add DMI] [Load DMI FILE] [Save DMI FILE]

  BIOS
  System
  Base Board
  Enclosure/Chassis
  Processor
  Memory Controller
  Memory Module
  Memory Module
  Memory Module
  Memory Module
  Cache
  Cache
  Port Connector
  Port Connector
  Port Connector
  Port Connector
  Port Connector
  Port Connector
  Port Connector
  System Slots

==== Display Component ====
Type : BIOS Information
Handle : 0000
Vendor Name : Award Software International, Inc.
BIOS Version : 4.51 PG
BIOS starting Address Segment : E000
BIOS Build Date : 05/12/97
BIOS Characteristics : Press [ENTER] for detail
Size of BIOS ROM : 0128K

←→ Move cursor ENTER=Accept DEL=Delete ESC=Abort&Exit

```


## Chapter 5

---

Use the ? ? (left-right) cursors to move the top menu items and the ?? (up-down) cursor to move between the left hand menu items. The bottom of the screen will show the available keys for each screen. Press enter at the menu item to enter the right hand screen for editing. “Edit component” appears on top. The reversed color field is the current cursor position and the blue text are available for editing. The orange text shows auto-detected information and are not available for editing. The blue text “Press [ENTER] for detail” contains a second pop-up menu is available, use the + - (plus-minus) keys to change the settings. Enter to exit and save, ESC to exit and not save.


If the user has made changes, ESC will prompt you to answer Y or N. Enter Y to go back to the left-hand screen and save, enter N to go back to left-hand screen and not save. If editing has not been made, ESC will send you back to the left hand menu without any messages.

### Add DMI



This DMI Configuration Utility also allows the system integrator or end user to add additional information into the DMI database such as serial numbers, housing configurations, and vendor information. Those information not detected by the motherboard BIOS and has to be manually entered through the DMI Configuration Utility and updated into the DMI database.

Load DMI File




You can load the disk file to memory by entering a drive and path and file name here.

## Chapter 5

---

### Save DMI File



You can save the DMI (normally only saved to flash ROM) to a file by entering the drive and path here. If you want to cancel save, you may press ESC and a message "Bad File Name" appears here to show it was not saved.



---

## APPENDIX A

## QUICK GUIDE

The table below summaries the functions and settings of each jumper of the motherboard.

Function		Jumper Settings	
<b>CPU Speed Selection</b>	Pentium II 233MHz	JP8:	1-2 open 3-4 open 5-6 close
	Pentium II 266MHz	JP8:	1-2 close 3-4 close 5-6 open
	Pentium II 300MHz	JP8:	1-2 open 3-4 close 5-6 open
	Pentium II 333MHz	JP8:	1-2 close 3-4 open 5-6 open
<b>Clear CMOS Data</b>	Clear	J11:	1-2 short
	Normal	J11:	2-3 short

**Appendix A**

---