12/5/22, 5:28 PM Untitled Document


The Wayback Machine - https://web.archive.org/web/20030428184048/http://www.protech.com.tw:80/product/e...



386SX-40 CPU Card







Specifications:

CPU Type: 386SX-40 on board

CPU Voltage: 5V CPU Frequency: 40MHz

Chipset: ALi M6117C

DRAM: 2 x 72-pin SIMM up to 32MB

I/O Chipset SMsC 669

BIOS: Phoenix-Award BIOS, Flash ROM

IDE Interface: 1 x ISA IDE

FDD Interface: 1

Serial Port: 2 x 16550 UART, COM2 for RS232/422/485

Parallel Port: 1 x parallel (SPP/EPP/ECP)

Watchdog: 16 level Watchdog Timer selectable w/ Reset/NMI

CMOS: Benchmarq

Keyboard: Mini DIN connector and external connector Mouse: Mini DIN connector (selectable w/ KB)

Speaker: Internal buzzer & external speaker connector

SSD 2 x 32-pin socket supports DOC up to 144MB each

Bus Interface ISA Bus, PC/104 Bus Power Supply Support AT power

Power

+5V

Requirement

Green Function Controlled by hardware and software

Dimension 185mm x 122mm, 7.28" x 4.8"

This site is best viewed in 800 * 600 true color with IE 5.0 copyright © 2003 Protech Systems Co., Ltd All rights reserved