



ENDURA GL815E

ATX Intel® 815E Chipset-Based PCI/ISA Motherboard

FEATURE SUMMARY

- Intel 815E chipset
- Integrated VGA
- Celeron processor in flip-chip (FC-PGA) package
- Intel Pentium III processor in (FC-PGA) package
- Up to 512MB SDRAM
- System Management
- Intel 10/100 Ethernet
- PanelLink™ flat panel interface
- DFP and DVI monitor support
- AC97 audio
- Fan control
- Eight GPIO lines
- Four PCI slots
- One ISA slot
- One shared PCI/ISA slot
- 4X AGP slot
- One parallel port
- Two serial ports
- Four USB ports
- PhoenixBIOS™
- Connectors for internal cabling
- 12" x 7.5"
- ATX 2.03 compliant
- ROHS Compliant



Endura motherboards are Intel® architecture motherboards designed specifically to meet the demands of the OEM embedded marketplace. Based on chipsets supplied by the Embedded Intel Architecture Division, Endura motherboards have an extended lifetime, unlike commercial motherboards which have typical lifetimes of six to twelve months. Combined with high quality design and manufacture, engineering change control, engineering support and product life cycle management, Endura motherboards provide the ideal solution for an embedded system where long lifetime and low cost of ownership are paramount. Endura motherboards also offer continued support for legacy features such as standard serial interfaces and hard-switched power supplies, which remain important for embedded applications.

The GL815E is a standard form factor, ATX motherboard that is well suited to embedded applications. It is available with either Intel Celeron™ or Pentium® III processor in FC-PGA package providing scalable performance and the option to choose the appropriate price/performance point to suit the application. The high degree of integration and rich feature set provides a platform that is ideal for low cost system design. The GL815E is designed for use in applications with a need for high performance graphics, which can be supported either with the integrated 815E video or by upgrading to a high performance AGP graphics card in the 4X AGP slot. Available in different build configurations, the GL815E is used in telecom, datacom, medical, transaction terminals (such as coin-op gaming) and industrial automation applications.

Endura GL815E Specifications

FEATURE	FUNCTION	DESCRIPTION
Processor	Socket	370-pin PGA ZIF for Intel Celeron and Pentium III processors in FC-PGA package
	FSB	66MHz, 100MHz, 133MHz operation
Chipset		Intel 815E chipset with ICH2
Memory	Type	Two 168-pin DIMM sockets for PC100 and PC133 SDRAM
	Capacity ECC/Parity	Maximum of 512MB Not supported
Video	Controller Display Cache Frame Buffer Flat Panel DFP/DVI	3D graphics controller integrated in 815E chipset Optional display cache via GPA module in the slot Stored in main memory (holds 2D and 3D data) Silicon Image SII164 PanelLink controller Cabled DVI or DFP connector from header Optional DVI or DFP adapter for rear I/O mounting
Audio	Controller	AC97 v2.1 CODEC using Analog Devices AD1885 (with integrated headphone amplifier)
	Connectors	ATAPI connector for CD-ROM (stereo) ATAPI connector for telephony (mono) 7-pin connector for external AC97 CODEC Stereo line out 3.5mm jack socket (can be used with headphones) Stereo line in 3.5mm jack socket Mono microphone 3.5mm jack socket with phantom power, suitable for electret microphones
Network	Controller	Intel ICH2 integrated MAC with Intel 82562 PHY
	Connector	IEEE 802.3 10Base-T and 100Base-TX compatible RJ45 with LEDs for line activity, link integrity and line speed
IDE	Devices	Two Ultra ATA/100 or ATA/66 interfaces via 40-way boxed header
	Types	Supports ATAPI, LS120 and ZIP drives
Floppy	Types	Supports standard 2- and 3-mode 3.5" floppy drive
Mechanical	Dimensions	12" x 7.5"
	Compliance PCB I/O shield	ATX 2.03 compliant Four layers Standard ATX available options for RJ45 Ethernet and DVI/DFP connectors
I/O	Parallel Port	25-pin D-type supporting bi-directional, EPP and ECP modes
	Serial Ports	COM1 on 9-pin D-type, COM2 via 10-way header
	IrDA	Supported in place of COM2 via front panel connector
	USB	Dual stacked USB 1.1 rear connector Motherboard header for single USB port USB interface via AGP slot Swappable PS/2 connectors
	Keyboard & Mouse	Phoenix keyboard code Motherboard headers for keyboard and mouse ports Eight GPIO lines for control functions or front panel indicators
Expansion Slots	PCI/ISA	Four dedicated bus master PCI 2.2 slots One ISA slot
	AGP	One shared PCI/ISA slot 4X AGP slot
System Management		Monitoring of voltage, temperature and fans Anti-tamper security CPU fansink and system fan speed control
Power Management		PCI PME, ACPI 1.0, APM 1.2
Power Supply	Type Typical	Support for hard- and soft-switched PSU 35W
Battery		Lithium coin cell (5 years operating life typical) Optional super-cap for 1 hour backup
BIOS	Type	PhoenixBIOS 4.0 Release 6.1
	Special Features	Customizable defaults, customer logo, silent boot, automatic configuration
Operating Systems		Windows® 95, Windows 98, Windows 2000, Windows NT® Qualification of real time and other operating systems subject to demand
Safety Compliance		Designed for compliance with UL1950, EN60950 and IEC60950
EMC Compliance		Designed for compliance with EN55022, EN55024 and FCC Part 15 Class B
Environment	Operating Temp	0°C to 55°C
	Storage Temp	-40°C to 85°C
	Relative Humidity	5% to 95% non-condensing

Ordering Information

Toll-Free: 800-950-0044

Phone: 503-615-1100

Support: 866-385-6167

Call for pricing and availability.
Refer to the order codes below.

DESCRIPTION

GL815E ATX with integrated DVI, RoHS

PRODUCT CODE: GLFPL03-0-0

I/O shield for GLFPL03-0-0, RoHS

PRODUCT CODE: ATX-FPL 81XIOSHLD

I/O shield for GLFPL03-0-0 (no DVI port), RoHS

PRODUCT CODE: ATX-L 81X IOSHLD

DVI connector / bracket assembly, RoHS

PRODUCT CODE: DVI_CABLE-R



Contact Information

www.radisys.com

info@radisys.com

Channels and other locations

Corporate Headquarters

5445 NE Dawson Creek Dr.

Hillsboro, OR 97124 USA

Phone: 503-615-1100

Fax: 503-615-1121

Toll-Free: 800-950-0044

Support: 866-385-6167

EMEA: +49 811 555457-0

China: 86.21.50804062

*2006 RadiSys Corporation. RadiSys is a registered trademark of RadiSys Corporation. Conveda, Microware and OS-9 are registered trademarks of RadiSys Corporation. Promentum, and Procelerant are trademarks of RadiSys Corporation. *All other trademarks are the properties of their respective owners. All specifications within this document are subject to change without notice.*