


# S755TWIN

**SiS 755 CHIPSET with AGP 8x slot /6-CH Audio /ATA133 /USB2.0/ Serial ATA/ LAN Support AMD Athlon64 ATX Main Board**

**2-Users /CPU 800MHz FSB /AGP 8X /Serial ATA /DDR400 /6-CH Audio /USB2.0 Solution**



6-Channel AC'97 Codec Support Front, Rear, Center-Base Speaker Output

**AGP 8X Slot**  
Support 4X/8X AGP VGA Card

**MagicTwin Connectivity**  
USB-to-PS/2 converter manages I/O devices and assigned user access

**Serial ATA**  
Support 2 Serial ATA port provided 150MB/s (Max.) transfer rate

With Y-cable support  
2-Keyboard, 2-Mouse for 2-Users function

**REALTEK RTL8201BL LAN PHYceiver**  
Supports 10/100 Mb/sec data transfer rate

**DDR Module Socket**  
Support DDR266/DDR333/DDR400 DRAM Max. 2GB

**ATA133 IDE Connector**  
Support 133MB/s data transfer rate

<p><b>Processor</b></p> <ul style="list-style-type: none"><li>- 64bit AMD Athlon64 754-Pin package utilizes Flip-Chip Pin Grid Array package processor, Support CPU Frequency 800MHz</li></ul> <p><b>Chipset</b></p> <ul style="list-style-type: none"><li>- SiS 755 K8HT AGP/MuTIOL Bridge (North Bridge) Chipset</li><li>- SiS 963L MuTIOL 1G Media I/O (South Bridge) chipset</li></ul> <p><b>Expansion Slot</b></p> <ul style="list-style-type: none"><li>- Support 5xPCI Slots, 1xCNR Slot</li><li>- 1xAGP Slot support AGP 8X</li></ul> <p><b>System Memory</b></p> <ul style="list-style-type: none"><li>- 2 x 184-pin DDR Module Socket Support Max 2GB DDR266/DDR333/DDR400 DRAM Module</li></ul> <p><b>Jumpless</b></p> <ul style="list-style-type: none"><li>- Support Jumpless function by BIOS SETUP let users more easier change the Frequency and ratio</li></ul> <p><b>Magic Setting</b></p> <ul style="list-style-type: none"><li>- Support CPU Front Side Bus step by step setting in BIOS SETUP let users have many choice when use over-clock function</li></ul> <p><b>Ultra DMA 133</b></p> <ul style="list-style-type: none"><li>- Support 2 x Ultra DMA 133 IDE Interface (Up to 4 IDE Devices &amp; 133MB/s transfer rate)</li><li>- ATAPI IDE CD-ROM, CD-R, CD-RW and LS-120 Support</li></ul>	<p><b>PC'99 Colorful I/O Ports</b></p> <ul style="list-style-type: none"><li>- 5xUSB2.0 Ports, 2xSerial Ports, 1xParallel Port</li><li>- 1xPS/2 Keyboard Port, 1xPS/2 Mouse Port, 1xFloppy Port</li><li>- 1xGame/MIDI port header/ Line-in/out /MIC Ports</li></ul> <p><b>2-Users Function</b></p> <ul style="list-style-type: none"><li>- With PS/2 Y-Cable support 2-Keyboard, 2-Mouse function</li><li>- Bundle MagicTwin Application Software support single PC system runs up to two stations in WindowsXP Operating System</li></ul> <p><b>On Board LAN</b></p> <ul style="list-style-type: none"><li>- Integrated LAN MAC with LAN PHYceiver</li><li>- Supports 10/100 Mb/sec data transfer rate</li></ul> <p><b>On Board Audio</b></p> <ul style="list-style-type: none"><li>- Software Audio Controller with Onboard 6-Channel CODEC Compliant to AC'97</li><li>- Support 3D Surround &amp; Positioning, Full Duplex</li></ul> <p><b>Serial ATA</b></p> <ul style="list-style-type: none"><li>- Support 2 Serial ATA Port provide 150MB/s (Max.) Data transfer rate</li><li>- Support RAID0, RAID1, RAID0+1 function</li></ul> <p><b>Dimension</b></p> <p>ATX form factor (30.5cm x 21.5cm)</p>	<p><b>Special Function</b></p> <ul style="list-style-type: none"><li>• ACPI supporting for OS Directed Power Management<ul style="list-style-type: none"><li>- MODEM Ring remote wake up</li><li>- RTC Alarm, wake On LAN, Keyboard Power On</li></ul></li><li>• PC Health Monitor CPU temperature, System temperature, System Voltage (Vcore, Vtt, 3.3V, 5V, 12V, .....), FAN speed</li><li>• <b>Power Fail Recovery support</b></li><li>• <b>Magic BIOS Utility support live Update BIOS function from web</b></li></ul> <p><b>Trademark</b></p> <ul style="list-style-type: none"><li>* Product and Company names mentioned herein may be the trademarks of their respective owners.</li></ul>
---	--	---