



**TI5ST**



Pentium SiS 5571 Single Chipset Motherboard with ATX Form Factor



**Processor**

Socket 7 for:  
Intel P54C or P55C (MMX) Processor, up to 200MHz  
AMD K5-PR, up to 166MHz  
Cyrix 6x86 or 6x86L, up to P166+  
IBM 6x86 and 6x86L, up to P166+

**Chipset**

SiS 5571 Chipset

**L2 Cache**

Onboard 256KB or 512KB (manufacturing option)

**System Memory**

Memory Capacity: 128MB  
Memory Sockets: Two 72-pin SIMMs and two 168-pin DIMMs  
Memory Types: FPM, EDO or SDRAM

**Onboard I/O**

Winbond 877 with:  
1 Floppy Controller (2.88MB)  
2 Serial Ports (16550 UART compatible)  
1 Parallel Port (ECP/EPP)

**Onboard IDE**

2 Channels of Bus Master IDE ports for up to four IDE devices  
PIO Mode 3 and 4 for up to 16.7MB/Sec  
DMA Mode 2 for up to 22MB/Sec

**USB Ports**

Two onboard USB headers

**BIOS**

1Mbit flash EPROM with:  
Plug and Play add-in card support

DMI support  
APM 1.2

**Expansion Slots**

Three PCI slots  
Two ISA slots  
One shared PCI/ISA slot

**Board Size**

ATX Form Factor



[Back to Product Line](#)



[Back to Home Page](#)

Copyright 1996 Taiwan Mycomp Co, Ltd. All Rights Reserved. Pentium and Pentium Pro are registered trademarks of Intel Corp. All other product and brand names are trademarks and/or registered trademarks of their respective companies.